

Jenway 4500 Series Conductivity Meters Continued

PJenway°

Model 4520

A high specification laboratory conductivity/resistivity/TDS/salinity and temperature meter that offers additional accuracy with 1, 2 or 3 point conductivity calibration across the wide measurement range of 0 to 19.99S. The dedicated "pure water" mode ensures the optimum accuracy for this difficult application.

- Conductivity, resistivity, TDS and salinity modes
- Special pure water mode for ultra low conductivity measurements
- Storage of 500 results with built in data logger
- · Infrared data link (IrDA) for connection to printer and RS232 link to connect to printer or PC via DataWay software

| | 4510 | 4520 | |
|--------------------------------|---|---|--|
| Conductivity Range | 6 auto-selected from 0 to 1999mS* | 6 auto-selected from 0 to 19.99S* | |
| Conductivity Resolution | 0.01µS to 0.01mS | 0.01µS to 0.01S | |
| Conductivity Accuracy | ±0.5% | ±2 digits | |
| Automatic std. recognition | 10µS, 84µS, 1 | 413µS, 12.88mS | |
| Cell constant | 0.010 to 19.999 | | |
| TDS Range | 6 auto selected from 0 - 1999g/L* | | |
| TDS Resolution (accuracy) | 0.01mg/L to 1g/L | _* (±0.5% ±2 digits) | |
| TDS Accuracy | ±0.5% | ±2 digits | |
| EC Ratio | 0.50 | to 0.80 | |
| Temperature Range, °C | -10 to 105 | | |
| Temperature Resolution, °C | 0.1 | | |
| Temperature Accuracy, °C | ±0.5 | | |
| ATC and Manual, °C | 0 to 100 | | |
| Temperature Coefficient, % /°C | 0.00 to 4.00 | | |
| Reference Temperature, °C | 18, 20 or 25 | | |
| Resistance Range, Mohm | _ | 0 to 20 | |
| Resistance Resolution, Mohm | _ | 0.01 | |
| Resistance Accuracy | _ | ±0.5% ±2 digits | |
| Salinity Range, g/L | _ | 0 to 99.9 | |
| Salinity Resolution, g/L | _ | 0.1 | |
| Salinity Accuracy | _ | 0-35 ±1g/L, 35-99.9 ±3g/L | |
| Cell Constant | 0.010 to 19.999 | | |
| GLP | _ | Calibration reminder interval (1 to 999hrs). Alarm outputs (open collector & audible) | |
| Outputs | Analogue and RS232 | Analogue, RS232 and IrDA interface | |
| Connector | 7 pin DIN | | |
| Power | 9V AC ±10% @ 50/60Hz | | |
| Dims, w x d x l, mm | 250 x 55 x 210 | | |
| Weight, g | 850 | | |
| Supplied with | Glass conductivity probe with ATC (K=1) (027 013), electrode holder | | |

^{*} With k = 10 cell

| Code | Alt Ref | Description | Price |
|---------|---------|-------------------------|---------|
| CON1220 | 451001 | 4510 conductivity meter | £673.00 |
| CON1230 | 452001 | 4520 conductivity meter | £908.00 |

Accessories

| Code | Alt Ref | Description | Price |
|---------|---------|------------------------------------|-------|
| CON1236 | 37702 | Replacement paper roll for printer | £8.00 |