Genlab Prime XL Large Capacity Incubators



As standard, the Prime XL range offers a mirror polished stainless steel interior, touchscreen control and an extended temperature range of 100°C.

- Mirror polished stainless steel internal chamber
- Temperature range: ambient +8 to 100°C
- Fluctuation: ±0.15°C @ 37°C
- On screen historical trending (48 hours)
- 8 stage profile control
- · Countdown timer
- 24/7 real time clock operation
- Increased ramp up/recovery times
- · Manual or automatic overheat reset
- High accuracy Pt100A duplex sensors <0.6°C
- Fan assisted circulation
- Excellent stability: <±0.5°C
- · Low chamber uniformity



Code	Alt Ref	Capacity, L	No. of Shelves	Shelf Positions	Ext Dims, w x d x h, mm	Price
INC2262	PRI/250H/TDIG	220	3	4	1090 x 570 x 1040	£4407.00
INC2264	PRI/350H/TDIG	320	3	4	1090 x 770 x 1040	£4655.00
INC2266	PRI/425H/TDIG	450	4	5	1350 x 810 x 1070	£5907.00
INC2268	PRI/500H/TDIG	535	5	7	1350 x 810 x 1270	£6397.00
INC2270	PRI/650H/TDIG	645	5	7	1570 x 950 x 1270	£8766.00
INC2272	PRI/750H/TDIG	750	5	8	1570 x 950 x 1420	£8006.00
INC2274	PRI/850H/TDIG	865	5	9	1570 x 950 x 1580	£9454.00
INC2276	PRI/1000H/TDIG	1050	5	11	1570 x 950 x 1780	£10521.00
INC2278	PRI/1250H/TDIG	1280	5	11	1870 x 950 x 1780	£11743.00

LEEC Classic Incubators



Incubators with fully sealed chambers manufactured from polished stainless steel with rounded corners for easy cleaning. The outer cabinet is manufactured from stainless steel, and has a tough powder coat paint finish, giving the incubator exceptional corrosion resistance. An inner glass viewing door closes positively onto a silicone gasket and the outer door has a magnetic gasket providing a good seal. A rear access port allows temperature monitoring probes to be inserted safely into the incubator chamber.

- Temperature range: ambient +5 to 60°C
- Fully sealed chamber
- Fan assisted air circulation
- Accurate temperature control
- Simple to operate
- Fast recovery time



Code	Description	Capacity, L	No. of Shelves	Ext Dims, w x d x h, mm	Int Dims, w x d x h, mm	Door Opening Recovery, mins	Price
INC1900	C100	100	2	684 x 620 x 582	550 x 500 x 365	2	£1541.00
INC1910	C157	157	4	684 x 620 x 790	550 x 500 x 573	3	£2051.00
INC1906	C330	330	6	684 x 620 x 1417	550 x 500 x 1200	4	£2864.00