BACK 2 BASICS 2021

Essentials for your laboratory including:

- Up to 33% OFF Eppendorf 5920R Refrigerated Centrifuges
- 33% OFF the NEW SLS Lab Basics Digital Orbital Shaker
- 20% OFF Eppendorf Move It® Multi-Channel Pipettes
- 50% OFF SLS Lab Basics my-FUGE 12 Place Centrifuges
- 30% OFF OHAUS Scout® Portable Balances
- 20% OFF NEW SLS Lab Pro Ultrasonic Baths

We stock the leading brands in laboratory supplies

eppendorf · SELECT · AXYGEN · BRAND · LAB PRO · national diagnostics · LAB BASICS · CORNING · GILSON · FLOWGEN · OHAUS · Lonza · meridian BIOSCIENCE · Jenway · METTLER TOLEDO · Benchmark Scientific · BUCHI · Haier Biomedical

Valid 1st June - 30th Sept 2021

SCIENTIFIC LABORATORY SUPPLIES

Welcome to the 2021 issue of BACK 2 BASICS

We work closely with a number of our key suppliers to bring you the best deals in the market for selected laboratory products. In this edition of BACK 2 BASICS we have fantastic offers on selected lines from our own SLS Lab Pro, SLS Select and SLS Lab Basics brands alongside those from world renowned manufacturers such as Meridian Bioscience, Eppendorf, Corning, Gilson, Mettler Toledo, Ohaus, Jenway, Haier and Benchmark.

To benefit from the prices offered in this brochure, please use the appropriate promotional code when placing your order.

In addition to the brochure, visit our website for supplementary 'BACK 2 BASICS EXTRA' online offers for even more great savings on many other fantastic products.

Please hurry, these discounts are only valid until **30th September 2021**.

Kind regards,
Scientific Laboratory Supplies (SLS)

SCIENTIFIC LABORATORY SUPPLIES

KEY to product symbols:

- NEW — New products
- 1 YEAR — Length of warranty
- Made in Britain
- Sustainability

DELIVERING PRECISELY THE QUALITY YOU NEED

Eppendorf 5920R Refrigerated Centrifuges

3 YEARS

eppendorf

Delivers extraordinary high capacity in a very compact and ergonomic product design. It has similar dimensions as competing refrigerated 3L models and yet features a superior capacity, making it the ideal instrument for high-throughput applications.

UP TO 33% OFF

Plus FREE point of use delivery (excluding islands, Highlands, Northern Ireland and the Republic of Ireland)

- Multi-lingual operating system, large backlit display, saves up to 99 user-defined programs
- FastTemp pro® function for automated pre-cooling
- High centrifugation speed of up to 21194xg (13700rpm)
- Aerosol-tight QuickLock® caps and lids
- Centrifuge lid with soft-touch lid closure
- Quiet operation to improve your work environment
- Automatic rotor recognition and imbalance detection
- Temperature range from –11 to 40°C



Code	Supplied with	List Price, £	Offer Price, £
B2B7362	S-4x1000 rotor, high-capacity buckets, adapters for 15/50mL conical tubes	11908.00	8928.00
B2B7364	S-4x1000 rotor, round buckets, adapters for 15/50mL conical tubes	12777.00	8624.00
B2B7366	S-4x1000 rotor, plate/tube buckets, adapters for 15/50mL conical tubes	11499.00	8624.00
B2B7368	S-4xUniversal-Large rotor, universal buckets, adapters for 13/16mm round-bottom tubes	11410.00	9128.00
B2B7370	S-4xUniversal-Large rotor, universal buckets, adapters for 5/15/25/50mL conical tubes and plates	12742.00	9368.00

Eppendorf Research Plus Move It® Multi-channel Pipettes with Adjustable Tip Spacing

NEW 3 YEARS

eppendorf

Do you frequently transfer samples between different vessel formats, such as between tubes and plates, and strive for more efficient and safe solutions? The new adjustable tip spacing pipette Move It® accelerates and simplifies synchronous pipetting of a series of samples. A unique design without tubing connections results in increased precision and durability as well as user and sample safety.

- Efficient sample transfers from one vessel type to another.
- Pre-defined settings allow for quick switches back and forth between different formats
- Time-saving thanks to rotatable pipette head – 360°
- Tubeless system for reliability and reproducible results- no cable tangle and tubing-porosity, for consistently reliable robustness and precision



Code	Channel	Volume Range, µL	Tip Spacing Range, mm	Colour Code	List Price, £	Offer Price, £
E3125000150	4	15 - 300	9 - 33	Orange	**1152.00**	919.00
E3125000184	4	120 - 1200	9 - 33	Dark green	**1152.00**	919.00
E3125000168	6	15 - 300	9 - 20	Orange	**1202.00**	956.00
E3125000192	6	120 - 1200	9 - 20	Dark green	**1202.00**	956.00
E3125000176	8	15 - 300	9 - 14	Orange	**1252.00**	996.00
E3125000206	8	120 - 1200	9 - 14	Dark green	**1252.00**	996.00

eppendorf

Free Delivery on ULT Freezers and CO_2 Incubators



Request a quote and receive FREE point of use delivery* on any Eppendorf F740/F570/F101 CryoCube ULT freezers or C170i CellXpert CO_2 incubators.

See website for full selection or contact your sales representative.

*excluding islands, Highlands, Northern Ireland and the Republic of Ireland

SCIENTIFIC LABORATORY SUPPLIES



KIMTECH™

Prizm

Multi-Layered Neoprene Nitrile Gloves

The perfect combination of precision, protection and comfort for the most demanding scientific applications

PRECISION

Ultra fingertip grip helps reduce risk of drops and breakage accidents in both wet and dry conditions

PROTECTION

Crafted with a proprietary combination of polymers with proven Type A chemical splash protection

COMFORT

US Ergonomics certified

For Scientists, By Scientists

Visit kimtech.eu to find out more

Kimberly-Clark PROFESSIONAL™

Unisex Howie Style Lab Coats



A unisex coat in white 245g/m² polyester cotton. The coats have an overlapped, studded front to allow quick removal and give extra protection.

- One jetted chest breast pocket
- Two jetted hip pockets
- Nine stud fastenings with broad underlay to avoid gaping
- Knitted cuffs
- Back darts

55% OFF

Code	Chest Size, cm	List Price, £	Offer Price, £
B2B06006	88	**32.80**	14.76
B2B06008	92	**32.80**	14.76
B2B06010	96	**32.80**	14.76
B2B06012	100	**32.80**	14.76
B2B06014	108	**32.80**	14.76
B2B06016	112	**32.80**	14.76
B2B06018	116	**32.80**	14.76
B2B06020	122	**32.80**	14.76



Meker Portable Burners

UP TO 70% OFF

Code	Description	List Price, £	Offer Price, £
B2B06102	Burner	**74.00**	33.60
B2B06104	Cartridge, 240g	**14.72**	4.42

EVO Line Waste Containers

NEW

Disposable containers for the disposal of special hospital and laboratory waste. Extremely solid and shock resistant at both high and low temperature, the containers of the EVO line guarantee a hermetic seal by means of the peripheral adhesive on the lid.

- Lateral and central handles tested for twice the max weight
- Stacking up to a maximum of 3m with full load
- High penetration resistance
- Maximum filling level indicator
- No emission of any harmful gas during the incineration process

UP TO 46% OFF



Code	Capacity, L	Lid	Ext Dims, w x d x h, mm	Max Load, kg	List Price, £	Offer Price, £
B2B7302	30	Single	400 x 300 x 330	15	**8.33**	5.47
B2B7306	50	Single	400 x 300 x 560	20	**10.50**	6.37
B2B7310	60	Single	400 x 300 x 650	25	**12.00**	6.44

SLS Select Centrifuge Tubes


- Certified RNase and DNase free
- Sterile
- Manufactured from high clarity medical grade polypropylene
- Leak proof flat polypropylene cap
- Printed graduations and a large writing area for sample identifications
- Racked tubes are packaged in recyclable card racks
- Lot traceability
- RCF: 9000 (15 and 50mL tubes)



Supplied in packs of 500

Code	Description	Volume, mL	List Price, £
SLS8102	Loose	15	**146.00**
SLS8103	Racked	15	**151.00**
SLS8106	Loose	50	**154.00**
SLS8110	Racked	50	**167.00**
SLS8114	Skirted, bagged	50	**177.00**

Slides with Ground Edge



SLS Select Slides with Ground Edge 76 x 26 x 1mm

LOW PRICE

Supplied in packs of 50

Code	Description	List Price, £
MIC2000	Plain	**2.10**
MIC2002	Twin frost	**2.30**

Forehead Thermometer



Infrared Forehead Thermometer

Fast and contactless, with blue backlit LCD display.

Code	List Price, £
COV1037	**19.95**

Parafilm® M Sealing Film

- Stretches up to 200% and clings even around irregular shapes and surfaces
- Free of plasticisers and consists primarily of polyolefins and paraffin waxes
- Conforms to the provisions of the US FDA when used below 55°C and observance of GMP (Good Manufacturing Practice)
- Resistant up to 48 hours against many polar substances e.g. saline solutions, inorganic acids and alkaline solutions
- Temperature range (continuous use): –45 to +50°C

UP TO 60% OFF



Code	Dims, mm x m	List Price, £	Offer Price, £
B2B06094	50 x 75	**55.00**	**23.10**
B2B06096	100 x 38	**61.00**	**24.40**
B2B06098	100 x 75	**99.00**	**41.60**
B2B06100	500 x 15	**119.00**	**50.00**

Swann-Morton Qlicksmart BladeFLASK Scalpel Blade Remover

A safe, quick and easy single-handed method for scalpel blade removal. The puncture proof sharps container shuts off automatically when it is full, and can be disposed of safely. Suitable for wall or surface mounting using the purpose designed bracket.



25% OFF

Code	Description	List Price, £	Offer Price, £
B2B06042	BladeFLASK scalpel blade remover	29.20	21.90
B2B06044	Mounting bracket	9.80	7.35

SLS Select Low Form Beakers

- Ideal for general laboratory use
- White graduations and marking spot
- Made from high quality borosilicate glass
- High chemical and thermal resistance
- Staple item of any laboratory
- Standards equivalent to ISO 3819



60% OFF

Code	Capacity, mL	Dims, Ø x h, mm	Pack	List Price, £	Offer Price, £
B2B06332	25	34 x 50	12	11.05	4.42
B2B06334	50	42 x 60	12	12.00	4.80
B2B06336	100	50 x 70	12	13.45	5.38
B2B06338	150	60 x 80	12	17.30	6.92
B2B06340	250	70 x 95	12	21.20	8.48
B2B06342	400	80 x 110	12	26.90	10.76
B2B06344	600	90 x 125	6	17.05	6.82
B2B06346	1000	105 x 145	6	25.20	10.08

SLS Select Conical Flasks

- With white graduations and marking spot
- Made from high quality borosilicate glass
- High chemical and thermal resistance
- Used for many laboratory applications
- Standards equivalent to ISO 1773

60% OFF



Code	Capacity, mL	Dims, h x Ø x neck Ø, mm	Pack	List Price, £	Offer Price, £
B2B06358	50	80 x 54 x 24	12	31.20	12.48
B2B06360	100	105 x 64 x 29	12	27.90	11.16
B2B06362	250	145 x 85 x 31	6	18.50	7.40
B2B06364	500	184 x 103 x 36	6	27.60	11.04
B2B06366	1000	131 x 214 x 42	6	39.40	15.76



Axygen® Microcentrifuge Tube Boxes

38% OFF

Polypropylene. -80 to 121°C. 100 x 1.5 to 2.0mL tube capacity. **Supplied in packs of 5**

Code	Colour	List Price, £	Offer Price, £
B2B7108	Assorted	46.40	29.00
B2B7110	Clear	41.80	26.10

SLS Select Media Bottles

- Perfect for everyday laboratory use
- Suitable for many applications, such as storage of culture media
- Made from high quality borosilicate glass 3.3 to ISO 3585
- Heat and chemical resistance
- GL45 blue polypropylene cap and pouring ring
- White graduations and marking spot
- Sloped shoulders for easy pour
- Standards to ISO 4796-1

Supplied in packs of 10



Code	Capacity, mL	Dims, Ø x h, mm	List Price, £	Offer Price, £
B2B06348	100	56 x 100	**28.80**	11.52
B2B06354	250	70 x 138	**55.00**	22.00
B2B06350	500	86 x 176	**32.80**	13.12
B2B06352	1000	101 x 225	**39.50**	15.80
B2B06356	2000	136 x 260	**119.00**	47.60



SLS Select Hand Sanitiser

70% alcohol gel, kills 99.9% of bacteria.

Code	Pack	List Price, £
COV1200	100mL	**0.59**
COV12000	10 x 100mL	**5.75**

SLS Select Cylinders

- Calibrated to Class B tolerances
- Can be used for many applications where a high accuracy level of volume measurement isn't critical
- Made from high quality borosilicate glass
- High chemical and thermal resistance
- Sturdy hexagonal glass base
- White graduations
- Standards equivalent to ISO 4788





Code	Capacity, mL	Height, mm	Pack	List Price, £	Offer Price, £
B2B06368	10	135	2	**6.00**	2.40
B2B06370	25	160	2	**6.80**	2.72
B2B06372	50	195	2	**7.92**	3.17
B2B06374	100	250	2	**9.52**	3.81
B2B06376	250	300	2	**16.25**	6.50
B2B06378	500	350	2	**24.80**	9.92
B2B06380	1000	430	Each	**18.45**	7.38

Gratnells Trays

5 YEARS

Gratnells
Everything in its place.

Handy trays with robust, polypropylene construction.



55% OFF

Code	Description	Colour	Dims, l x w x h, mm	List Price, £	Offer Price, £
B2B06082	F1 shallow	Royal blue	427 x 312 x 75	**7.00**	3.15
B2B06084	F1 shallow	Flame red	427 x 312 x 75	**7.00**	3.15
B2B06086	F1 shallow	Translucent	427 x 312 x 75	**7.00**	3.15
B2B06090	F2 deep	Royal blue	427 x 312 x 150	**11.76**	5.29
B2B06092	F2 deep	Flame red	427 x 312 x 150	**11.76**	5.29
B2B06088	F2 deep	Translucent	427 x 312 x 150	**11.76**	5.29

SLS Select BenchSafe Bench Protection

SLS SELECT

Strong, tear-resistant, waterproof polyethylene surface.

60% OFF



Code	Description	Dims, w x l, mm	Pack	List Price, £	Offer Price, £
B2B06046	BenchSafe	490 x 50000	1 roll	**175.00**	70.00
B2B06048	BenchSafe	460 x 570	50 sheets	**185.00**	74.00
B2B06050	BenchSafe	600 x 490	100 sheets	**180.00**	72.00
B2B06052	BenchSafe Plus	600 x 490	50 sheets	**140.00**	56.00

Plastic Tray Trolleys

- Lightweight
- Supplied with precision bearing castors including 2 brakes
- Ergonomic in design and attractive in appearance
- Heavy duty construction from high quality, nylon fibre blended polymers

UP TO 30% OFF



Code	Shelves	Dims, w x d x h, mm	Platform Dims, mm	Max Load, kg	List Price, £	Offer Price, £
B2B06076	3	460 x 750 x 980	630 x 424	150	**143.00**	107.00
B2B06078	2	460 x 750 x 940	630 x 424	100	**121.00**	91.00
B2B06080	2	513 x 990 x 970	866 x 500	250	**253.00**	177.00

BRAND Transferpette® S Pipette Kits

Precise and easy to use, the Transferpette® S air displacement pipette allows you to work efficiently and ergonomically with both small and large volumes. Low operating forces and a short stroke ensure relaxed pipetting, even during long pipetting series. The volume-change protection is also easy to operate with gloves on and protects your set volume against accidental adjustment.

40% OFF

- Colour code on volume adjustment wheel, shaft and volume-change protection
- Can be calibrated easily and without tools thanks to Easy Calibration technology
- Slim shaft for sampling from narrow vessels (centrifuge tubes)



Code	Description	Contains	List Price, £	Offer Price, £
B2B7280	Starter kit micro	3 x pipettes (0.1-25µL, 0.5-10µL, 10-100µL); 3 x TipBox pipette tips (2 x 0.5-20µL, 1 x 2-200µL); 3 x shelf mounts	**674.00**	404.00
B2B7282	Starter kit midi	3 x pipettes (2-20µL, 20-200µL, 100-1000µL); 3 x TipBox pipette tips (2 x 2-200µL, 1 x 50-1000µL), 3 x shelf mounts	**637.00**	382.00
B2B7284	Starter kit macro	3 x pipettes (100-1000µL, 500-5000µL, 1000-10000µL); 3 x TipBox pipette tips (50-1000µL, 0.5-5mL, 1-10mL); 3 x shelf mounts	**674.00**	404.00
B2B7286	Starter kit standard	3 x pipettes (0.5-10µL, 10-100µL, 100-1000µL); 3 x TipBox pipette tips (0.5-20µL, 2-200µL, 50-1000µL); 3 x shelf mounts	**653.00**	392.00
B2B7288	Package 1	5 x pipettes (0.1-25µL, 0.5-10µL, 2-20µL, 20-200µL, 100-1000µL); 3 x TipBox pipette tips (0.5-20µL, 2-200µL, 50-1000µL); benchtop rack for 6 pipettes	**1100.00**	660.00
B2B7290	Package 2	5 x pipettes (0.5-10µL, 10-100µL, 20-200µL, 50-1000µL, 500-5000µL); 4 x TipBox pipette tips (0.5-20µL, 2-200µL, 50-1000µL 0.5-5mL); benchtop rack for 6 pipettes	**1100.00**	660.00

SLS Select Reagent Reservoirs

- "V" shaped well design for maximum reagent recovery
- Easy to read graduation markings located on the top edge with a fill line on inner walls
- Drip free pour-off spouts at every corner
- Manufactured in a clean room with sterile versions certified as RNase/DNase and pyrogen free
- Wide base for stability
- Tiered wall design prevents deformation when handling and reduces the chance of spills
- Nesting design allows easy separation that reduces the chance of warping or damage
- Lot numbers indicated on sterile versions
- Polystyrene

35% OFF



Code	Capacity, mL	Sterility	Inner Pack	Pack	List Price, £	Offer Price, £
B2B06039	25	Sterile	1	100	**87.00**	57.00
B2B06041	25	Sterile	5	200	**105.00**	68.00
B2B06043	25	Non sterile	Bulk	100	**37.00**	24.00
B2B06045	50	Sterile	1	100	**90.00**	59.00
B2B06047	50	Sterile	5	200	**111.00**	72.00
B2B06049	50	Non sterile	Bulk	100	**39.00**	25.40
B2B06051	100	Sterile	1	100	**107.00**	70.00
B2B06053	100	Sterile	5	200	**126.00**	82.00
B2B06055	100	Non sterile	Bulk	100	**41.00**	26.70

SLS Lab Pro Variable Volume Pipettes

3 YEARS

The SLS Lab Pro pipettes offer superior quality at an affordable price. These are lightweight pipettes with a handle that fits naturally in the hand. They feature a volume locking system for safe, secure pipetting. A lubricated piston assembly offers very light pipetting forces.

- Adjustable tip ejector button to adapt to both right and left-handed users
- Clip mechanism allows easy and safe removal of tip ejector



UP TO 53% OFF



Code	Channel	Volume Range, µL	List Price, £	Offer Price, £
B2B06292	Single	0.2 - 2	**210.00**	105.00
B2B06294	Single	1 - 10	**210.00**	105.00
B2B06296	Single	2 - 20	**210.00**	105.00
B2B06298	Single	10 - 100	**210.00**	105.00
B2B06300	Single	20 - 200	**210.00**	105.00
B2B06302	Single	100 - 1000	**210.00**	105.00
B2B06304	Single	500 - 5000	**240.00**	120.00
B2B06306	Single	1000 - 10000	**240.00**	120.00
B2B06308	8	0.5 - 10	**495.00**	235.00
B2B06310	8	2 - 20	**495.00**	235.00
B2B06312	8	20 - 200	**495.00**	235.00
B2B06314	8	20 - 300	**495.00**	235.00
B2B06316	12	0.5 - 10	**565.00**	285.00
B2B06318	12	2 - 20	**565.00**	285.00
B2B06320	12	20 - 200	**565.00**	285.00
B2B06322	12	20 - 300	**565.00**	285.00

National Diagnostics AquaPor Agarose

Extremely reliable and convenient agaroses that dissolve easily with low boil over to produce clear, strong gels. Genetic Technology Analysis Certified (GTAC). Certified DNase, RNase, and protease free.

UP TO 49% OFF



Code	Description	Pack	List Price, £	Offer Price, £
B2B7042	AquaPor LE agarose (low EEO)	500g	**725.00**	367.00
B2B7044	AquaPor LM agarose (low melting temperature)	100g	**710.00**	384.00

SLS Lab Basics Variable Volume Pipettes

3 YEARS

Single Channel:

- Ergonomic design ensuring light weight & soft plunger movement
- Click-stop system for volume selection
- Colour coded for easy identification
- Calibration conforms to EN-ISO 8655 with report enclosed with every pipette

Multi Channel:

- Smooth and light tip loading and ejection
- Leak free sealing of tips
- Manifold is easily removable, fully autoclavable and can rotate 360° for easy right or left hand operation



UP TO 69% OFF

Code	Channel	Volume Range, µL	Compatible Tips	List Price, £	Offer Price, £
B2B06156	Single	0.1 - 2.5	10µL/10XL	**115.00**	46.00
B2B06158	Single	0.5 - 10	10µL/10XL	**115.00**	46.00
B2B06160	Single	2 - 20	10XL	**115.00**	46.00
B2B06162	Single	5 - 50	20µL/100µL	**115.00**	46.00
B2B06164	Single	10 - 100	100µL/200µL	**115.00**	46.00
B2B06166	Single	20 - 200	200µL/300µL	**115.00**	46.00
B2B06168	Single	100 - 1000	1000µL/1250µL	**115.00**	46.00
B2B06170	Single	500 - 5000	—	**138.00**	52.00
B2B06172	Single	1000 - 10000	—	**138.00**	54.00
B2B06174	8	0.5 - 10	10µL/10XL	**520.00**	159.00
B2B06176	8	5 - 50	20µL/100µL	**520.00**	159.00
B2B06178	8	10 - 100	100µL/200µL	**520.00**	159.00
B2B06180	8	20 - 200	200µL/300µL	**520.00**	159.00
B2B06182	8	30 - 300	200µL/300µL	**520.00**	159.00

SLS Lab Basics Bottle Top Dispensers

2 YEARS A

Ergonomically designed for easy use and outstanding performance, in addition to being extremely durable and reliable. Calibrated in ISO 17025 accredited calibration facility.

- Fully autoclavable
- Easy re-calibration: a single tool to recalibrate
- Volume lock: smooth and accurate volume setting
- Universal bottle adaptor: comes with 4 additional adaptors for regular bottle sizes
- Uncomplicated mounting: snap-fit mounting of discharge tube

48% OFF



Code	Volume Range, mL	Graduations, mL	List Price, £	Offer Price, £
B2B06184	1 - 10	0.2	**184.00**	95.00
B2B06186	2.5 - 30	0.5	**210.00**	110.00
B2B06188	5 - 60	1.0	**210.00**	110.00

Corning® Lambda™ Plus Pipette Starter Kit

Engineered to provide the highest levels of accuracy, reproducibility, and comfort. Features smooth plunger movement and extremely low pipetting forces. A locking mechanism prevents accidental change to the volume setting. Designed to maintain their calibration, even after repeated use and autoclaving. A key is included with each pipette for easy in-house calibration.

- Factory calibrated to strict ISO 8655 standards
- Fully autoclavable and UV resistant
- Designed for universal fit with all common brands of pipette tips
- Adjustable tip ejector

45% OFF

Includes: 4 x single-channel pipettes (0.5 to 10µL, 2 to 20µL, 20 to 200µL, 100 to 1000µL), universal carousel rack for 6 single channel pipettes, 3 x Corning DeckWorks™ pipette tips (10µL, 200µL, 1000µL).



Code	List Price, £	Offer Price, £
B2B06428	670.00	368.00

Corning® Lambda™ EliteTouch™ Pipette Starter Kit

Engineered to provide the highest level of ergonomic, accuracy, and precision. Features smooth plunger movement and extremely low pipetting forces to reduce wrist strain and fatigue (RSI). Coloured pushbuttons (included) can help define user or application for sample safety and lower risk of cross contamination.

- Ergonomic handle design for perfect fit for both right and left hand
- Convenient one-hand volume setting with auto-lock system
- 4-digit counter for greater precision, perfectly positioned for visibility at all times
- Fully autoclavable and UV resistant
- Easy in-lab calibration helps you quickly adjust your pipettor to various liquid types
- Individually tested and supplied with a certificate of quality

46% OFF

Includes: 4 x single channel pipettes (0.5 to 10µL, 2 to 20µL, 20 to 200µL, 100 to 1000µL), universal linear stand for 4 single channel pipettes, 3 x Corning® DeckWorks pipette tips (10µL, 200µL, 1000µL), 4 x 3 x coloured pushbuttons.



Code	List Price, £	Offer Price, £
B2B06432	754.00	406.00


Gilson PIPETMAN® M Connected Pipettes

1 YEAR

PIPETMAN® M Connected bluetooth enabled electronic pipettes that offer accuracy and precision in both standard and repetitive pipetting modes. Connect the pipette to the Gilson PipetteScope™ app and know exactly when the pipette needs to be calibrated, access service history reports and gain visibility of the pipette usage analytics. With the PIPETMAN® M Connected software, create custom protocols. Used together with TRACKMAN® Connected, the pipette interacts in real time with the device to plan, execute and track pipetting protocols.

- Motorised piston allows for high pipetting reproducibility and accuracy
- Requiring virtually no pipetting forces to aspirate and dispense samples
- Helps reduce pipetting fatigue and increase pipetting efficiency

Code	Model	Channel	Volume Range, µL	List Price, £	Offer Price, £
B2B7146	P10M	Single	0.5 - 10	**469.00**	266.00
B2B7148	P20M	Single	2 - 20	**469.00**	266.00
B2B7150	P100M	Single	5 - 100	**469.00**	266.00
B2B7152	P200M	Single	20 - 200	**469.00**	266.00
B2B7154	P300M	Single	20 - 300	**469.00**	266.00
B2B7156	P1200M	Single	100 - 1200	**469.00**	266.00
B2B7158	P5000M	Single	500 - 5000	**469.00**	266.00
B2B7160	P10mLM	Single	1000 - 10000	**469.00**	266.00
B2B7162	P8x10M	8	0.5 - 10	**865.00**	490.00
B2B7164	P8x20M	8	1 - 20	**972.00**	552.00
B2B7166	P8x100M	8	10 - 100	**865.00**	490.00
B2B7168	P8x200M	8	20 - 200	**972.00**	552.00
B2B7170	P8x300M	8	10 - 300	**865.00**	490.00
B2B7172	P8x1200M	8	50 - 1200	**972.00**	552.00
B2B7174	P12x10M	12	0.5 - 10	**865.00**	490.00
B2B7176	P12x20M	12	1 - 20	**972.00**	552.00
B2B7178	P12x100M	12	10 - 100	**865.00**	490.00
B2B7180	P12x200M	12	20 - 200	**972.00**	552.00
B2B7182	P12x300M	12	10 - 300	**865.00**	490.00
B2B7184	P12x1200M	12	50 - 1200	**972.00**	552.00



UP TO 43% OFF

Up to 6 week lead time

Accessories

TRACKMAN® Connected is a tablet designed to communicate with Gilson's PIPETMAN® M Connected via Bluetooth, improving efficiency by tracking pipetting tasks. The tablet interacts in real-time with the pipette and guides the user through their protocol with the PipettePilot™ app.

Code	Description	List Price, £	Offer Price, £
B2B7186	PIPETMAN® M electronic charging carousel for 5 pipettes	**392.00**	294.00
B2B7188	TRACKMAN® connected tablet	**1495.00**	1121.00

Gilson PIPETMAN® M Connected Packages

1 YEAR

Promotional packages below featuring combinations of pipettes and accessories.

Code	Description	Contains	List Price, £	Offer Price, £
B2B7190	Single channel pipette package	PIPETMAN® M electronic charging carousel for 5 pipettes, 3 x PIPETMAN® M single channel pipettes	**1571.00**	1069.00
B2B7192	8 channel pipette package	TRACKMAN® Connected tablet, PIPETMAN® M electronic charging carousel for 5 pipettes, 1 x PIPETMAN® M 8 channel pipette, and 2 x PIPETMAN® M single channel pipettes	**3061.00**	2059.00
B2B7194	12 channel pipette package	TRACKMAN® Connected tablet, PIPETMAN® M electronic charging carousel for 5 pipettes, 1 x PIPETMAN® M 12 channel pipette, and 2 x PIPETMAN® M single channel pipettes	**3154.00**	2109.00



Pipettes

Choose the appropriate number of PIPETMAN® M Connected pipettes from the list below to complete your chosen package.

Code	Channel	Model	Volume Range, µL
B2B7320	Single	P10M	0.5 - 10
B2B7322	Single	P20M	2 - 20
B2B7324	Single	P100M	5 - 100
B2B7326	Single	P200M	20 - 200
B2B7328	Single	P300M	20 - 300
B2B7330	Single	P1200M	100 - 1200
B2B7332	Single	P5000M	500 - 5000
B2B7334	Single	P10mLM	1000 - 10000
B2B7336	8	P8x10M	0.5 - 10
B2B7338	8	P8x20M	1 - 20
B2B7340	8	P8x100M	10 - 100
B2B7342	8	P8x200M	20 - 200
B2B7344	8	P8x300M	10 - 300
B2B7346	8	P8x1200M	50 - 1200
B2B7348	12	P12x10M	0.5 - 10
B2B7350	12	P12x20M	1 - 20
B2B7352	12	P12x100M	10 - 100
B2B7354	12	P12x200M	20 - 200
B2B7356	12	P12x300M	10 - 300
B2B7358	12	P12x1200M	50 - 1200

SLS Select Serological Pipettes

- Manufactured in compliance with the current versions of the ISO 13485 and FDA CFR 21 Part 820, cGMP
- Made from USP Class VI polystyrene resin
- Crisp, dark ascending and descending as well as negative graduations
- Colour-coded rings for easy identification
- Plugged
- Non-pyrogenic
- RNase-/DNase-free
- Sterile



60% OFF

Code	Volume, mL	Packaging	Inner Pack	Pack	List Price, £	Offer Price, £
B2B06382	1	Individual	100	1000	**144.00**	57.00
B2B06384	1	Bulk	25	1000	**119.00**	47.20
B2B06386	2	Individual	100	1000	**157.00**	63.00
B2B06388	2	Bulk	25	1000	**118.00**	47.20
B2B06392	5	Individual	50	200	**43.00**	17.20
B2B06390	5	Bulk	25	500	**112.00**	44.80
B2B06394	10	Individual	50	200	**45.00**	18.00
B2B06396	10	Bulk	25	500	**137.00**	55.00
B2B06400	25	Individual	50	200	**103.00**	41.20
B2B06398	25	Bulk	20	200	**159.00**	58.00
B2B06402	50	Individual	20	100	**126.00**	50.00

SLS Lab Basics Pipette Filler

5 YEARS

Lightweight, UV resistant material, featuring adjustable valves and 3 modes (high, low, gravity). Filling and dispensing speed is easily set using the same hand by pressing the large mode button. Uses standard 0.45µm hydrophobic filters. Supplied with charger, bench stand, magnetic /fixable wall mount and 5 coloured nose cones.

50% OFF



Code	List Price, £	Offer Price, £
B2B06190	**200.00**	100.00

Corning® Stripettor™ Ultra Pipette Controller

Featuring conveniently positioned switches change operating modes and speeds and a LCD display for continuous visualisation of speed, modes, and battery status. Supplied with with universal power supply, 3 x 0.2µm filters, 3 x coloured nose pieces and wall hanger.

49% OFF



Code	List Price, £	Offer Price, £
B2B06430	**275.00**	140.00

SLS Select PES Syringe Filters

The highly asymmetrical pore structure of PES membranes offers an excellent loading capacity and high flow rate for these naturally hydrophilic syringe filters. Moulded in a polypropylene shelter.

- Diameter: 25mm
- Sterile
- Recommended for preparation of protein samples, ultra-fast filtration of tissue culture media

Supplied in packs of 50, individually wrapped

69% OFF



Code	Pore Size, µm	List Price, £	Offer Price, £
B2B06412	0.22	**64.00**	20.00
B2B06414	0.45	**64.00**	20.00



HygienePak

2 x 3-ply face masks (type IIR), 2 x 1.5mL 70% alcohol gel sachets, 3 x anti-bacterial wipe sachets.

Code	List Price, £
COV1128	**0.99**

SLS Select Qualitative Filter Paper Discs, Grade A

The most widely used general purpose filter paper for general applications in laboratory analysis and liquid clarification. Medium filtration velocity and retention.

- Whatman Grade 1 equivalent
- 160µm thickness
- 5 - 13µm nominal retention

Supplied in packs of 100

50% OFF



Code	Ø, mm	List Price, £	Offer Price, £
B2B06206	55	**4.00**	2.00
B2B06208	70	**4.40**	2.20
B2B06210	90	**5.10**	2.55
B2B06212	110	**6.00**	3.00
B2B06214	125	**6.20**	3.10
B2B06216	150	**8.80**	4.40
B2B06218	185	**13.10**	6.55
B2B06220	240	**21.20**	10.60

SLS Lab Basics my-FUGE 12 Place Centrifuge

2 YEARS

LAB BASICS

Eliminate the need to change rotors when switching between microtubes and PCR strips with the unique COMBI-Rotor™ (included) allowing the running of 12 x 1.5/2.0mL microtubes and 4 PCR strips simultaneously. With a fixed speed that produces 2000xg, this centrifuge is perfect for quick spin downs.

- Twice the capacity of most mini centrifuges
- Near silent operation
- Starts and stops with closing/opening of the lid
- Conserves valuable bench space





Code	Max Speed, RPM	Max RCF, g	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7092	5500	2000	146 x 203 x 108	**471.00**	236.00

SLS Lab Basics Mini Centrifuge

2 YEARS

LAB BASICS

Ideal for microfiltration and quick spin downs from the walls and caps of microcentrifuge tubes. The compact design saves bench space and features an easy-open clear lid. Simply close the lid for acceleration and open the lid for deceleration, or alternatively use the on/off switch to control.

- Easy-to-use with dual start/stop function
- Compact design
- Whisper quiet operation
- Ideal for quick spin downs of microtubes and PCR tubes
- Universal voltage
- Rotor change without tools
- Accelerates and brakes in seconds
- Supplied with 8 place 1.5/2.0mL microtube rotor and 16 place (2 x 8 strips) PCR rotor





Code	Max Speed, RPM	Max RCF, g	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06202	7000	2680	160 x 170 x 122	**166.00**	89.00

SLS Lab Basics 12 Place Microcentrifuge

2 YEARS

Compact and powerful high-speed centrifuge, ideal for research applications including sedimentation of cells and viruses and isolation of macromolecules such as DNA, RNA, proteins or lipids. It consists of a large LCD display which provides all visual information and a unique cooling design which minimises rotor heating.

- Whisper quiet operation - less than 49dB
- Automatic door lock
- Automatic internal diagnosis
- Polypropylene rotor is fully autoclavable
- Run time: 30 sec - 99 min
- Pulse operation for quick spins
- Sound-alert function
- Over-temperature and over-speed detector
- Supplied with 12 position 1.5/2.0mL microtube rotor

55% OFF



Code	Max Speed, RPM	Max RCF, g	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06204	15000	15100	245 x 255 x 140	**1099.00**	490.00

SLS Flowgen Plate Spinner

2 YEARS

Rapidly spin down droplets in PCR or microplates to improve PCR yields or give more consistent assay results. The swing out rotor has two plate carriers that rest at a 75° angle. This allows plates to be inserted confidently without sealing tapes or caps. Most samples can be spun down in less than 20 seconds. To end a run, simply open the lid and the automatic, electric brake brings the rotor to a quick, smooth stop in just 4 seconds.

- Unique swing-out rotor design prevents spillage
- Accepts most types of PCR plates
- Capacity: 2 x PCR plates (when stacking skirted PCR plates, max. capacity is 4 plates); 2 x microplates
- Remarkably small footprint

44% OFF



Code	Max Speed, RPM	Max Speed, x g	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06236	2550	600	230 x 260 x 197	**745.00**	415.00

OHAUS Frontier™ FC5706 Multi Centrifuge

2 YEARS

Reliable compact low-speed general purpose centrifuges. The standard rotor options can process both round and conical bottom tubes (including common blood tubes), and can also be adapted easily with accessories to process smaller tubes.

- Intuitive interface
- Compact profile helps to save valuable bench space in labs
- Easy installation design
- Brushless quiet motor
- Timer: 10s to 99h 59m 59s; continuous
- 2 line backlit LCD display
- Dims, w x d x h: 291 x 392 x 266mm
- Max speed: 6000rpm/4427rcf



30% OFF

Code	Description	List Price, £	Offer Price, £
B2B7206	FC5706 Frontier™ multi centrifuge	**1145.00**	802.00
B2B7208	FC5706 Frontier™ multi centrifuge with rotor angle 12 x 15mL (for round/conical bottom tubes)	**1290.00**	903.00
B2B7210	Rotor angle 6 x 50mL (for round/conical bottom tubes)	**483.00**	338.00

Corning® LSE Mini Microcentrifuge

2 YEARS

A compact, lightweight and easy-to-use centrifuge. It includes an 8-place rotor that will accept standard 1.5 to 2.0mL microcentrifuge tubes with adapters for 0.5/0.4mL and 0.2mL tubes, and a 4 place rotor for PCR strip tubes.

- Close the lid to start, press the lid release button to stop
- Quick release rotor system eliminates the need for tools to exchange rotors
- Electronic braking provides rapid deceleration for more efficient sample prep
- Compact, rugged design withstands heavy use in crowded lab environment
- Dual lid switch provides safe operation
- Ergonomic design allows for comfortable handling



29% OFF

Code	Max Speed, RPM	Max RCF, g	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7112	6000	2000	148 x 174 x 122	**197.00**	139.00

SLS Flowgen 3D MiniMixer

2 YEARS

Multi-functional shaker which provides a 3-dimensional "nutating" motion for thorough, foam-free mixing in blood and centrifuge tubes, as well as in a variety of flat vessels. Feature maintenance free, brushless motors capable of loads up to 2kg and are safe for use in cold rooms and incubators.

- Includes dimpled mat; ideal for mixing in blood & centrifuge tubes
- Optional flat mats are also available for mixing other vessel types
- Stacking platforms sold separately, effectively doubling the usable surface area
- Tri-directional motion for thorough, uniform mixing



35% OFF

Code	Speed, RPM	Tilt Angle, °	Platform Dims, mm	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7082	24 (fixed)	20	270 x 190	270 x 190 x 200	**399.00**	259.00

SLS Flowgen 2D BenchRocker

2 YEARS

Designed to provide the precise speeds and tilt angles required for a broad range of molecular and biological mixing applications. The user can adjust both parameters to match the vessel size and the volume of liquid being mixed, yielding optimum results. Provides a gentle wave effect for non-foaming mixing, as is required for most blot washing and gel work. When set to higher speeds and more extreme tilt angles, they produce aggressive agitation for vigorous sample mixing.

- Accepts stackable platforms (clearance = 70mm)
- Adjustable speed and tilt for a wide range of applications
- Dual platform accessory doubles work surface
- Cold room and incubator safe

35% OFF



Code	Speed Range, RPM	Tilt Angle, °	Platform Dims, mm	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7080	2 - 30	0 - 30	350 x 300	350 x 300 x 200	**749.00**	487.00

SLS Lab Basics Vortex Mixer 2 YEARS

Compact and stable design with electronic speed control ensures the same speed is maintained at all times, even during changes of load and also features continuous or touch operation. The orbital diameter of 4mm provides effective and efficient mixing inside the sample.

- Quiet and compact stable design
- Continuous or touch operation
- Electronic speed control for constant speed even during changes in load
- Aluminium cast base with silicone feet for excellent stability and vibration damping



50% OFF


Code	Speed Range, RPM	Dims, w x d x h, mm	Weight, kg	List Price, £	Offer Price, £
B2B06222	0 - 2500	127 x 160 x 130	3.5	**200.00**	100.00

SLS Lab Basics DigiRoll 6 Tube Roller 2 YEARS

6 tube roller providing a rocking and rolling motion for optimum mixing of viscous samples. Equipped with a powerful brushless DC motor for maintenance free long life and quiet operation. Microprocessor controller gives accurate speed under variable load, and the programming feature means the user can save and run up to 9 user defined programs.

- Digital display with soft touch keypad
- IP 21 protection class
- Timer from 1 min to 99 min and infinite mode
- User can set pulse time from 30 to 99 seconds
- Adjustable rollers spacing to hold different diameter tubes
- Stackable design with robust construction

33% OFF



Code	Capacity	Speed Range, RPM	Tilt Angle, °	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06224	15 x 3/4mL tubes	10 - 80	±3	502 x 301 x 93	**450.00**	300.00

SLS Lab Basics Digital Orbital Shaker

NEW 5 YEARS

LAB BASICS

A dependable and versatile shaker for a vast range of protocols. Create your own matrix for vessels of all shapes and sizes with hi-lo platform and bungee cords. Instantly adjusts to weight load changes and unbalanced loads with no-stop electronic motor feedback allowing for truly reproducible results.

- Durable ABS construction suitable for use in incubators (excluding CO_2) and cold rooms within 2 to 40°C; 20 to 80% RH, non-condensing
- Run time: 0 to 74 hours and 59 minutes, 1 second increments or continuous
- Soft start and shut down feature reduces spilling from full vessels
- Designed to handle heavy loads up to 4.5kg
- Overload protection shut-off prevents overloading
- Supplied with skid-free rubber platform mat, 8 x bungee cords, universal hi-lo platform with soft rubber edge bumpers, power adapter (110–240VAC, 50/60 Hz) with 4 interchangeable plug types

33% OFF



Code	Orbit, mm	Speed Range, RPM	Platform Dims, mm	Dims, l x w x h, mm	List Price, £	Offer Price, £
B2B7300	19	20 - 300	279 x 279	314 x 197 x 314	**750.00**	500.00

Grant PMS-1000i Microplate Shaker

2 YEARS

grant

Microplate shaker providing reliable, regulated shaking for two or four microplates. With a speed range of 150 to 1000rpm, the PMS-1000i can be adjusted to suit the application – gentle shaking to ensure that the well contents are not ejected, or more vigorous agitation for effective aeration across the small surface area of each of the wells.

- Direct drive mechanism and brushless motor
- Set and display the speed
- Quick and easy screw fitting of any standard-depth 96- or 384-well plate
- Continuous or timed operation, with automatic switch off
- Easy-to-use integral electronic timer
- Quick and easy to use screw fittings keep the plates securely in position
- Easy to read LED display clearly indicates time and speed
- Simple graduated dial to adjust the speed to suit the application
- Comes with FREE platform for 4 plates worth £47!

Plus FREE platform - Savings of £110!



15% OFF

Code	Speed Range, RPM	Orbit, mm	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7138	150 - 1200	2	220 x 205 x 90	**418.00**	355.00

SLS Lab Basics Hotplate Stirrer, 280°C

Stainless steel stirrer with a ceramic coated hotplate which resists corrosion. Features a digital control system, ideal for use in physics, chemistry and biotech labs.

- Heating temperature up to 280°C
- LED display shows temperature and speed
- 50°C HOT warning indicates residual hotplate temperature
- ABS chemical resistant casing
- Includes FREE external temperature sensor PT1000 and support clamp

44% OFF



Code	Stirring Capacity, L	Speed Range, RPM	Max Temp, °C	Plate Ø, mm	List Price, £	Offer Price, £
B2B06238	3	100 - 1500	280	135	347.00	195.00

SLS Lab Basics Hotplate Stirrer, 340°C

Stirrer hotplate with ceramic coated stainless steel plate, widely used in chemical synthesis, physical and chemical analysis, bio-tech labs.

- Simple running interface easy to use and program, automatically identifies temperature sensor PT1000 and transfers to PT1000 operation mode
- LCD display shows target and actual temperatures, as well as set and actual speed
- Brushless DC motor - maintenance free and explosion-proof
- Fully closed assembly guarantees safety and long service life, effectively prevents the liquid damage
- HOT warning indicates residual hotplate temperature
- Includes FREE external temperature sensor PT1000 and support clamp

47% OFF



Code	Stirring Capacity, L	Speed Range, RPM	Max Temp, °C	Plate Ø, mm	List Price, £	Offer Price, £
B2B06240	20	100 - 1500	340	135	607.00	320.00

OHAUS Guardian 5000 Hotplate Stirrers

2 YEARS

Ensure consistent stirring performance and temperature control. With the LCD display, and chemical resistant SmartHousing™ that is easy to clean and remains cool to the touch. SafetyHeat™ protects the lab with its early detection system to continuously monitor the electronics and shut off heating before an over temperature condition occurs.

- LCD display
- Audible alarm
- Green indicator lights for heating/stirring
- Speed range: 60 - 1600rpm
- Temperature range: +5 to 500°C

30% OFF



Code	Function	Capacity, L	Plate Dims, mm	Plate Material	List Price, £	Offer Price, £
B2B7196	Hotplate	15	178 x 178	Ceramic	**313.00**	219.00
B2B7198	Stirrer	15	178 x 178	Ceramic	**313.00**	219.00
B2B7200	Hotplate stirrer	15	178 x 178	Ceramic	**398.00**	279.00
B2B7202	Hotplate stirrer	18	254 x 254	Ceramic	**565.00**	396.00
B2B7204	Hotplate stirrer	20	Ø 135	Aluminium	**398.00**	279.00

SLS Flowgen Mini Digital Dry Bath

2 YEARS

With its compact construction, broad temperature range, and multiple block options, the digital mini block is the perfect tool for laboratory incubations. The simple touch pad controls and a digital display provide for "set and walk away" temperature selection and unrivalled accuracy.

- Exchangeable blocks for 0.2 to 50mL tubes (sold separately)
- Clear cover ensures temperature uniformity
- Simple touchpad, digital control
- Supplied with block lifter

50% OFF



Code	Temp Range, °C	Accuracy, °C	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7086	Ambient +5 - 100	±0.5	105 x 150 x 115	**355.00**	178.00

SLS Flowgen Digital Dry Baths

2 YEARS

Digital dry baths with accurate "set and walk away" digital temperature selection, eliminating the need for external thermometers and repetitive "fine tuning" of a temperature control knob. Simply enter the desired temperature on the digital touchpad and the dry bath provides accurate temperature with real time monitoring that continuously maintains the selected temperature.

- Assorted blocks for a wide variety of tube sizes (sold separately)
- Include an easy to use block lifter with a temperature insulated handle
- Built-in user re-calibration function, to guarantee long term temperature accuracy
- Temperature range: ambient +5 to 150°C
- Temperature accuracy: ±0.2°C, increments: 0.1°C, uniformity: ±0.2°C
- Digital timer is built into the touchpad display (1 to 999 minutes)

35% OFF



Code	No. Block Positions	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7088	1	200 x 230 x 80	**440.00**	286.00
B2B7090	2	220 x 260 x 80	**549.00**	357.00

SLS Lab Pro Safevac Aspiration System

2 YEARS

- Designed for laboratory waste recovery and separation of liquid and solid
- Vacuum power can be set to different levels to achieve 1 - 15mL/s aspirating speed
- Sensitive level sensor to prevent liquid overflow during operation
- Waste bottle, tubing and handle are fully autoclavable
- Wide range of adapters to fit tubes and microplates

50% OFF



Code	Vacuum Range, mbar	Vacuum Speed, mL/S	Volume, L	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06242	0 - 600	1 - 15	4	180 x 240 x 450	**1200.00**	600.00

SLS Flowgen MultiSUB Horizontal Electrophoresis Tanks

2 YEARS

MultiSUB Midi has been designed for routine horizontal gel electrophoresis. This unit is ideal for those routinely checking medium numbers of samples over short to medium gel run lengths. Loading guides allow easy well identification and sample loading. Complete with 2 x 16 sample combs, loading guides and dams.

MultiSUB Choice offers a wide degree of versatility. Three tray options are available allowing the choice of one, two or all three gel length options. Maximising comb and tray options allow up to 210 samples to be resolved per gel. The 15cm total run length allows restriction fragment or other close MW sample bands to be easily separated and identified. Supplied with 2 x 20 sample combs, loading guides and dams.

40% OFF



Code	Description	Gel Dims, w x l, mm	Sample Capacity	Buffer Volume, mL	List Price, £	Offer Price, £
B2B06228	Midi	100 x 100	100	300	**347.00**	208.00
B2B06230	Choice	150 x 70, 150 x 100, 150 x 150	210	500	**428.00**	257.00

SLS Flowgen OmniPAGE Mini Vertical Electroblotting Systems


2 YEARS

Simple, versatile vertical mini gel electrophoresis, combining both functionality and ease of use. The OmniPAGE mini is a high quality, low cost product with unsurpassed finish, durability and strength. It features injection moulded construction for leak proof running, and a simple clamp system to ensure a tight seal between buffer chambers to prevent current leakage.

OmniPAGE Mini system is supplied with glass plates with bonded 1mm thick spacers, 2 x 12 sample combs, cooling pack, blanking plate and casting base.

OmniPAGE Mini PAGE and blotting package is supplied with PAGE insert, 2 x 2mm thick notched glass plates, 2 x 2mm thick plain glass plates with 1mm thick bonded spacers, 1x dummy plate, 2 x combs (1mm thick 12 samples), 1 x casting base, silicone mat, cooling pack, standard electroblotting module (includes mini platinum wire, blotting insert, 4x 10 x 10cm compression cassettes and 16 x fibre pads).

40% OFF



Code	Description	List Price, £	Offer Price, £
B2B06232	OmniPAGE Mini PAGE and blotting package	**921.00**	553.00
B2B06234	OmniPAGE Mini system with castor	**623.00**	374.00

SLS Flowgen Electrophoresis Power Supplies

2 YEARS

NanoPAC is an ultra-compact and economical unit, featuring a simple two step feature to set a programmable change in voltage/current/time during the run to provide increased versatility. The user-friendly interface has a conspicuous 3-digit LED, and is easily adjustable in 1V and 1mA increments, making it perfect for separations where precise settings are required.

PowerPro is a versatile multi-function power supply suitable for a wide range of electrophoresis applications, with nearly twice the current and power of the market leading equivalent unit. Featuring both built-in pre-set and customisable protocols; a 2.4" TFT-LCD screen displays the current running parameters and allows the user to browse pre-set and saved protocols. The convenient pause/resume key allows any run to be temporarily halted for inspection of the gel and restarted from the same position.

30% OFF



Code	Description	Max Current, mA	Max Power, W	Max Voltage, V	Output Pairs	List Price, £	Offer Price, £
B2B06632	NanoPAC	400	60	300	2	**380.00**	266.00
B2B06634	PowerPRO	700	150	300	5	**436.00**	305.00

Lonza FlashGel™

The FlashGel™ system for fast electrophoresis of DNA is the ideal tool for quick screening of up to 32 samples without having to plan your day around agarose gels. Contains all you need to quickly begin using FlashGel™ cassettes. The FlashGel™ system is the fastest way to separate DNA and the best way to watch DNA migration as it happens. This revolutionary new tool separates DNA in 2 - 7 minutes. Monitor gel runs right at the bench, without UV light. The highly sensitive system allows a 5-20x reduction in DNA levels - saving both time and money. FlashGel™ cassettes contain precast, prestained agarose gels and buffer - no need for gel preparation, buffer addition or gel staining.

- 5 minute separation and recovery, See bands in as little as 2 minutes
- Recover samples directly without UV light band excision or purification
- Real-time separation and documentation
- Watch band migration as it happens
- Photograph gels at the bench without DNA damaging UV light
- Outstanding sensitivity and resolution

15% OFF



Code	Description	Contains	List Price, £	Offer Price, £
B2B06862	Device pack	Dock, camera, power supply	**1994.00**	1695.00
B2B7024	Starter pack	Dock, cassettes (1.2% 12+1 single-tier, 9 pack), loading dye, marker (100 - 4000bp)	**786.00**	668.00
B2B7026	DNA kit	Cassettes (1.2% 12+1 single tier, 9 pack), loading dye, marker (100 - 4000bp)	**492.00**	418.00

Meridian Bioscience HyperLadder™ Markers

Molecular weight markers composed of a restriction digest plus one or more PCR products, especially designed for easy size determination of linear double-stranded DNA fragments on 1% to 2% TAE or TBE agarose gels. The ready-to-use format reduces handling steps and saves time.



- Broad size range
- Easy to orientate - several brighter reference bands
- Stable
- Supplied with a 5x loading dye for loading of sample DNA

Code	Description	Size	List Price, £	Offer Price, £
B2B7022	HyperLadder™ 25bp - 12 bands from 25bp to 500bp	100 lanes	**63.00**	54.00
B2B7008	HyperLadder™ 25bp - 12 bands from 25bp to 500bp	200 lanes	**107.00**	91.00
B2B7010	HyperLadder™ 25bp - 12 bands from 25bp to 500bp	500 lanes	**236.00**	201.00
B2B7018	HyperLadder™ 50bp - 15 bands from 50bp to 2000bp	100 lanes	**59.00**	50.00
B2B7012	HyperLadder™ 50bp - 15 bands from 50bp to 2000bp	200 lanes	**100.00**	85.00
B2B7014	HyperLadder™ 50bp - 15 bands from 50bp to 2000bp	500 lanes	**224.00**	190.00
B2B7020	HyperLadder™ 100bp - 10 bands from 100bp to 1kb	100 lanes	**49.00**	41.70
B2B7004	HyperLadder™ 100bp - 10 bands from 100bp to 1kb	200 lanes	**94.00**	80.00
B2B7006	HyperLadder™ 100bp - 10 bands from 100bp to 1kb	500 lanes	**211.00**	179.00
B2B7016	HyperLadder™ 1kb - 14 bands from 200bp to 10kb	100 lanes	**43.00**	36.60
B2B7000	HyperLadder™ 1kb - 14 bands from 200bp to 10kb	200 lanes	**63.00**	54.00
B2B7002	HyperLadder™ 1kb - 14 bands from 200bp to 10kb	500 lanes	**113.00**	96.00

National Diagnostics ProtoGel

Forms an electrophoresis matrix that is ideal for the separation of proteins and polypeptides. Stabilised, ready-to-use, acrylamide/methylene bisacrylamide solution (37.5:1 ratio), with zero acrylic acid content and oxidation products such as aldehydes.





Code	Description	Pack	List Price, £	Offer Price, £
B2B7032	Protogel 30% solution	1L	**107.00**	45.50
B2B7034	Protogel 40% solution	1L	**128.00**	80.00

National Diagnostics SequaGel Accugel

Stabilised, ready-to-use solution of 40% (w/v) premixed acrylamide: bisacrylamide solution. Zero acrylic acid content, and oxidation products such as aldehydes have been removed. Formulated with 18 MegOhm water, 0.2 Micron filtration.





Code	Description	Pack	List Price, £	Offer Price, £
B2B7036	19:1 monomer solution (40%)	1L	**93.00**	60.00
B2B7038	29:1 monomer solution (40%)	1L	**96.00**	55.00

Jenway 7315 Spectrophotometer 3 YEARS

Jenway

Spectrophotometer with icon driven software and easy and intuitive navigation system. Features measurement modes for absorbance, % transmittance, concentration, spectrum scanning, kinetics and quantitation, and an easy access USB port on the front of the unit which enables results to be stored directly to a USB memory stick for easy transfer of data. Can also store up to 240 methods which can be copied from one unit to another using the USB capability. Enhanced security features enabling the settings and methods to be locked preventing unauthorised changes to the instrument settings and method parameters.

- Icon driven software
- Results and method saving to USB memory stick
- Autologging capabilities
- Press to read xenon lamp
- Fitted with 10x10mm cuvette holder, supplied with 100 disposable cuvettes, instruction manual, universal power supply, USB memory stick, PC software on CD ROM and interface cable



20% OFF

Code	Wavelength Range, nm	Wavelength Accuracy, nm	Bandwidth, nm	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7106	198 - 1000	±2	5	275 x 400 x 220	**3670.00**	2936.00

Jenway 6850 Spectrophotometer 1 YEAR

Jenway

Double beam spectrophotometer with a variable spectral bandwidth. The highly stable optics and two detectors measure the sample and reference simultaneously optimising measurement accuracy. Measurement modes for photometrics, concentration, multi-wavelength, spectrum scanning, kinetics, quantitation, DNA/RNA and protein analysis. Includes Jenway Prism PC software, offering additional functionality with preloaded methods for DNA/RNA and protein analysis, extensive post-measurement tools, unlimited results saving and easy export of data.

- Variable spectral bandwidth 0.5, 1, 2, 4, 5nm
- Integrated user interface
- USB port for data storage
- Conforms to European Pharmacopeia requirements
- Supplied fitted with single 10x10mm cuvette holder in sample and reference position, instruction manual, power cables, PC software on CD ROM with USB connection cable and dongle, 4GB USB memory stick, 2 x quartz cuvettes, 4 x glass cuvettes, dust cover and 230V power supply

20% OFF



Code	Wavelength Range, nm	Wavelength Accuracy, nm	Bandwidth, nm	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7102	190 to 1100	±0.3 (at 0.5 and 1nm), ±0.5 (at 2, 4 and 5nm)	Variable 0.5, 1, 2, 4, 5	600 x 450 x 200	**7318.00**	5854.00


NEW

Cole-Parmer® stuart™

antylia SCIENTIFIC

The Best In Class

Cole-Parmer® Stuart™ Undergrad Hotplate




The re-designed Cole-Parmer® Stuart™ Undergrad hotplates include Analogue and Digital hotplates, stirrers, and hotplate stirrers - available in a choice of metal coated or ceramic tops. All hotplates are completely glazed with BioCote® treatment for antimicrobial protection.

Mettler Toledo FiveEasy™ Benchtop Meters

1 YEAR

Ideally suited for applications in the laboratory, the FiveEasy™ and FiveEasy™ Plus benchtop instruments provide high quality pH/mV or conductivity measurements with the simple click of a button. Compact in design, and featuring various data export opportunities, the FiveEasy™ series instruments are the perfect companion to get reliable measurement data, all at a reasonable price.

- Large, well-structured display with intuitive button arrangement and simple menu
- Compact design saves space
- FiveEasy™ Plus meters allow data to be exported either directly to a printer or a PC



UP TO 24% OFF

Supplied with FREE electrode worth up to £135!

	FiveEasy™ F20 pH/mV	FiveEasy Plus™ FP20 pH/mV	FiveEasy™ F30 Conductivity	FiveEasy Plus™ FP30 Conductivity
Measuring Range	0 to 14pH -2000 to 2000mV 0 to 100°C	-2 to 16 pH -2000 to 2000mV -5 to 105°C	0.00 to 200mS/cm 0.00 to 200g/L 0.0 to 100°C	0.01 to 500mS/cm 0.00 to 300g/L 0.00 to 42psu -5 to 105°C
Accuracy	±0.01pH ±1mV ±0.5°C	±0.01pH ±1mV ±0.3°C	±0.5% of the measured value ±0.5°C	±0.5% of the measured value ±0.3°C
Calibration	Max. 3 points	Max. 5 points	1 point	1 point

Code	Meter Model	Description	Free Electrode	List Price, £	Offer Price, £
B2B7234	FiveEasy F20 pH/mV	Sandard kit	LE438 electrode	**476.00**	360.00
B2B7236	FiveEasy Plus FP20 pH/mV	Standard kit	LE438 electrode	**601.00**	497.00
B2B7238	FiveEasy Plus FP20 pH/mV	Bio kit	LE410 electrode	**627.00**	497.00
B2B7240	FiveEasy Plus FP20 pH/mV	Micro kit	LE422 electrode	**632.00**	497.00
B2B7242	FiveEasy Plus FP20 pH/mV	Tris kit	LE420 electrode	**611.00**	497.00
B2B7244	FiveEasy F30 conductivity	Standard kit	LE703 electrode	**698.00**	621.00
B2B7246	FiveEasy Plus FP30 conductivity	Standard kit	LE703 electrode	**835.00**	723.00

SLS Select pH Buffer Solutions

NIST Traceable

Code	Description	Colour Code	Pack	Offer Price, £
F152000	Buffer solution pH 4	Red	500mL	3.99
F151668	Buffer solution pH 4	Red	1L	5.99
F152002	Buffer solution pH 7	Yellow	500mL	3.99
F151671	Buffer solution pH 7	Yellow	1L	5.99
F152004	Buffer solution pH 10	Blue	500mL	3.99
F151674	Buffer solution pH 10	Blue	1L	5.99

Honeywell

Spend & Save



On Honeywell products*

Place your order on the **SLS** website and quote 'HONEY30' to receive

30% off

*Offer excludes all Hydranal products

SCIENTIFIC LABORATORY SUPPLIES

ExitusPlus™ Decontamination Solutions

PanReac AppliChem ITW Reagents

Eliminate DNA/RNA or RNAse contamination in your lab



Enabling trueness and reliability for your COVID-19 / PCR analysis

Supplied in 500mL spray bottles

Code	Description	For	List Price, £	Offer Price, £
B2B7372	DNA-ExitusPlus™ indicator free	DNA/RNA decontamination	80.00	56.00
B2B7374	RNase-ExitusPlus™	RNase decontamination	80.00	56.00

Corning® 3D Clear Tissue Clearing Reagent

Designed specifically to support imaging for 3D cell culture models and plate-based high-throughput processing. When paired with fluorescent labelling (e.g. fluorescent protein, immunofluorescence, chemical dyes) and high content confocal microscopy, it allows for complete 3D cell culture model characterisation and more accurate drug screening.

- Rapid tissue clearing
- Easy to use
- No special equipment required
- Compatible with IF, FP and other fluorescent labels
- Microplate and automation compatible
- Reversible to follow up with 2D H&E/IHC



UP TO 14% OFF

Code	Pack	List Price, £	Offer Price, £
B2B7114	10mL	140.00	120.00
B2B7116	30mL	342.00	296.00
B2B7118	100mL	934.00	810.00

First Aid Offers

See our website for product details and full list of contents.

UP TO 15% OFF



Code	Description	List Price, £	Offer Price, £
B2B7050	Redcap™ eye wash and skin flush kit for acid/ alkali splashes in aura box	37.70	32.00
B2B7052	Burns first aid kit in aura box	31.30	26.60
B2B7054	Hydrofluoric acid treatment kit in aura box	15.59	13.25
B2B7056	Dependaplast pilfer proof plaster dispenser	17.08	14.52
B2B7058	BS8599-1 workplace first aid kit in aura box - small	19.77	16.80
B2B7060	BS8599-1 workplace first aid kit in aura box - medium	29.30	24.90
B2B7062	BS8599-1 workplace first aid kit in aura box - large	37.50	31.90
B2B7064	Biohazard clean-up kit in aura box - 5 applications	14.63	12.43
B2B7066	Eye wash point with mirror	13.20	11.22
B2B7068	Deluxe eye wash station in aura box	20.50	17.43
B2B7070	Mediana A15 HeartOn automated external defibrillator	1433.00	1290.00

SLS Lab Basics Inverso TC100 Inverted Microscopes

1 YEAR

Ideal for the typical working laboratory and is built to a high-quality specification. It is robust enough to withstand the rigours of constant daily use and with a quintuple position nose-piece fitted as standard, it is ideally suited for multiple observation techniques and/or magnifications.

- Trinocular head inclined at 45°
- Eyepieces: 10/20mm wide field
- Objectives: 4X, 40X plan-achromatic LWD/10X, 20X, 40X Phase Contrast
- Condenser: NA 0.3 (removable), working distance 72mm
- Stage: 160 x 250mm with additional mechanical stage (2 interchangeable stage plates) stage extending board
- Focusing: coaxial coarse and fine
- Illumination: 3W LED
- Epi fluorescence module adds blue excitation (460-490nm) and green excitation (480-550nm)

UP TO 40% OFF



Code	Description	List Price, £	Offer Price, £
B2B06416	With mechanical stage LED	3335.00	2000.00
B2B06418	With epi fluorescence module	10571.00	7400.00

SLS Lab Basics Tablet Microscope Camera

Tablet camera designed for microscopy applications with a high-definition 9.7" colour LCD touchscreen. Equipped with software that allows the user to preview an image, set the white balance, capture images and videos as well as having measurement and annotation capabilities.

- Crystal display, RK3066 dual-core 1.5Hz CPU
- Touch-screen operation, can be used as a small computer
- Includes Wi-Fi and Bluetooth wireless networking for easy file, HDMI output

32% OFF

Supplied with FREE C-mount adapter for SLS Lab Basics Inverso micro-scopes, worth £145!



Code	Camera	List Price, £	Offer Price, £
B2B06420	15fps at 1024 x 768; 1/2.5 (4:3) 5mpx CMOS	956.00	650.00

59% OFF



SLS Select Lens Cleaning Tissue

Ideal solution for cleaning lenses and other optical surfaces made from glass, quartz or plastic.

Supplied in packs of 50

Code	Dims, mm	List Price, £	Offer Price, £
B2B06248	80 x 100	4.90	2.00

SLS Lab Basics Compact Precision Balances

5 YEARS

LAB BASICS

- Accurate, high quality, attractive, and stackable units
- Perfect for applications where portability or easy storage are paramount
- External calibration
- Supports multiple weighing units like counting, % weighing
- Hygienic and rustproof stainless steel pan
- Security slot at the back for wire-locking to prevent theft
- Power supply: AC adaptor or 4 AA size dry batteries (batteries not included)

46% OFF



Code	Capacity, g	Readability, g	List Price, £	Offer Price, £
B2B06024	310	0.01	**260.00**	140.00
B2B06026	3100	0.1	**260.00**	140.00

SLS Lab Pro P-Series Precision Balances

5 YEARS

LAB PRO

- One touch automatic calibration
- Compact, B5 size footprint
- Fast, 1 second stabilisation
- Large bright vacuum fluorescent display
- Shock absorber function
- Multiple weighing units
- GLP/GMP/GCP/ISO compliant
- Statistical calculation function
- ACAI – Automatic Counting Accuracy Improvement
- Dims, w x d x h: 193 x 262.5 x 85.5mm



50% OFF

Code	Capacity, g	Readability, g	Plate Ø, mm	List Price, £	Offer Price, £
B2B06114	122	0.001	130	**856.00**	428.00
B2B06116	220	0.001	130	**882.00**	441.00
B2B06254	320	0.001	130	**914.00**	457.00
B2B06118	520	0.001	130	**1045.00**	523.00
B2B06120	1220	0.01	150	**856.00**	428.00
B2B06122	2200	0.01	150	**882.00**	441.00
B2B06256	3200	0.01	150	**914.00**	457.00
B2B06290	5200	0.01	150	**1045.00**	523.00

SLS Lab Pro A-Series Analytical Balances

5 YEARS

- Compact footprint
- Breeze break with rotary doors that slide behind the balance and can be removed with one touch
- Ideal for applications where space is at a premium
- Reverse backlit LCD display for easy to read weighing results
- Statistical calculation function eliminates the need for a stats printer
- Standard RS-232C
- Fast, compact SHS sensor, response time ~2 seconds

40% OFF



Code	Capacity, g	Readability, mg	Calibration	List Price, £	Offer Price, £
B2B06106	102	0.1	External	**856.00**	514.00
B2B06250	102	0.1	Internal	**1040.00**	624.00
B2B06108	152	0.1	External	**934.00**	560.00
B2B06110	152	0.1	Internal	**1092.00**	655.00
B2B06112	252	0.1	External	**1097.00**	658.00
B2B06252	252	0.1	Internal	**1313.00**	789.00

OHAUS Scout® SKX Portable Precision Balances

2 YEARS

Portable precision balances with large backlit LCD. Built to endure demanding applications with superior overload protection. Features including faster stabilisation time, increased capacity, multiple connectivity options and stackable design make Scout the best weighing experience.

30% OFF



- Integrated overload protection system rated at ten times the capacity
- Large backlit display improves readability in low light conditions
- High-strength stainless steel pan and an impact-resistant plastic pan support
- 4 clearly marked buttons remove complexity, and guide you quickly and easily
- Ingenious draftshield (0.001g model only) was designed with an easy to remove top cover piece

Code	Capacity, g	Readability, g	Platform Dims, mm	List Price, £	Offer Price, £
B2B7212	120	0.001	Ø 93	**374.00**	262.00
B2B7214	220	0.01	Ø 120	**249.00**	174.00
B2B7216	420	0.01	Ø 120	**302.00**	211.00
B2B7218	620	0.01	Ø 120	**332.00**	232.00
B2B7220	1200	0.01	170 x 140	**379.00**	265.00
B2B7222	2200	0.01	170 x 140	**441.00**	309.00
B2B7224	420	0.1	Ø 120	**177.00**	124.00
B2B7226	620	0.1	170 x 140	**203.00**	142.00
B2B7228	2200	0.1	170 x 140	**265.00**	186.00
B2B7230	6200	0.1	170 x 140	**338.00**	237.00
B2B7232	8200	1	170 x 140	**265.00**	186.00

OHAUS Scout® STX Portable Precision Balances

2 YEARS

High-performance portable balances with intuitive touchscreens for high accuracy and productivity. Featuring a slim design which allows stackable storage. Geared for superior performance with fast stabilisation time and high resolution weighing results, these portable balances set a new standard for a broad range of weighing applications. Features also include superior overload protection, multiple application modes and expanded connectivity options.

- 4.3" full-colour TFT graphic LCD touchscreen
- Advanced weighing technology allows for one-second stabilisation time for increased productivity
- Integrated overload protection system
- Mains or battery powered
- Draftshield protects the sample, increasing speed and repeatability (0.001g models only)

30% OFF



Code	Capacity, g	Readability, g	Platform Dims, mm	List Price, £	Offer Price, £
B2B4872	120	0.001	Ø 93	**535.00**	375.00
B2B4874	220	0.001	Ø 93	**600.00**	420.00
B2B4876	220	0.01	Ø 120	**383.00**	268.00
B2B4878	420	0.01	Ø 120	**436.00**	305.00
B2B4880	620	0.01	Ø 120	**483.00**	338.00
B2B4882	1200	0.01	170 x 140	**540.00**	378.00
B2B4884	2200	0.01	170 x 140	**600.00**	420.00
B2B4886	420	0.1	Ø 120	**234.00**	164.00
B2B4888	620	0.1	170 x 140	**265.00**	186.00
B2B4890	2200	0.1	170 x 140	**383.00**	268.00
B2B4892	6200	0.1	170 x 140	**510.00**	357.00
B2B4894	8200	1	170 x 140	**363.00**	254.00

SLS Flowgen Incu-Shaker™ Incubated Shaker

2 YEARS

Compact shaking incubator with a remarkably small footprint. Accepts several platforms and a variety of flasks, tubes and other common vessels. The standard platform (included) features a non-slip, rubber coated surface, ideal for tissue culture flasks, Petri dishes and staining trays.

- Extremely compact, just 280mm wide
- Touch screen control over time, speed and temperature
- Horizontally circular 19mm orbit for aeration & mixing
- Instantly exchange flask clamps with MAGic Clamp™ accessories
- Program STEP feature for linking consecutive programs



34% OFF

Code	Temp Range, °C	Speed Range, RPM	Orbit, mm	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7084	Ambient +5 - 70	30 - 300	19	280 x 480 x 330	**2909.00**	1925.00

Pulse 150 Ultrasonic Homogenizer with 6mm Horn and Soundproof Box

2 YEARS

Benchmark Scientific

- Ideal for cell disruption, DNA shearing and ChIP assays
- Programmable with touch screen control and pulsed operation
- 150W, for volumes 0.1 to 150 ml (requires appropriate horn)
- Supplied complete with 6mm horn, temperature probe and soundproof enclosure

30% OFF



Code	Power, W	Frequency, KHz	Volume, mL	List Price, £	Offer Price, £
B2B7252	1.5 - 150	20 - 25	0.1 - 150*	**2899.00**	2029.00

***Dependent upon installed horn, supplied with 6mm horn for volumes 10 - 100mL**

SLS Lab Pro BeadBug Microtube Homogeniser

2 YEARS

LAB PRO

High energy benchtop homogeniser that sets the performance standard for personal sized cell disruption and lysis instruments. The optimised mixing motion causes rapid cell disruption through constant high velocity impact from the hardened micro-beads chosen specifically for your sample type. Developed for samples too tough to be homogenised in a common lab vortexer, the BeadBug™ provides a convenient and economical alternative to the traditional, high capacity homogenisers on the market today.

- Extremely powerful mixing for lysis, grinding or homogenisation
- Faster and more effective than tissue grinders
- Homogenise up to 3 samples in disposable 2mL screw cap microtubes
- Extremely compact
- Eliminates the cross contamination

35% OFF



Code	Speed Range, RPM	Capacity	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7094	2800 - 4000	3 x 2mL	170 x 210 x 135	**848.00**	551.00

SLS Lab Pro Type 2 and 3 Water Purification Systems

SLS Lab Pro water purification system available in two water quality versions:

Type 3 – Primary grade water (reverse osmosis) suitable for glass washers, autoclave feed, stability chambers and steam/humidity generators.

Type 2 – General laboratory grade water (deionisation) for buffer, reagent and media preparation, sample dilution, general chemistry and teaching applications.

- Low cost, one box solution
- Wall or bench mounted
- 50% recovery rate keeps water costs to a minimum
- Energy consumption <60W
- Unique disposable RO maintains peak efficiency
- Consumables changed in seconds
- Built-in 35L reservoir
- Easy to install, low maintenance
- Minimal water wastage
- Mercury free UV

UP TO 37% OFF



Code	Model	Make Up Rate, L/hr	List Price, £	Offer Price, £
B2B7316	Choice 10 type 2 (DI)	10	**3824.00**	2600.00
B2B7074	Choice 10 type 2 (DI) UV	10	**4126.00**	2675.00
B2B7072	Choice 10 type 3 (RO)	10	**3510.00**	2375.00
B2B7314	Choice 10 type 3 (RO) UV	10	**3813.00**	2593.00
B2B06262	Choice 20 type 2 (DI)	20	**4132.00**	2600.00
B2B06264	Choice 20 type 2 (DI) UV	20	**4435.00**	2850.00
B2B06258	Choice 20 type 3 (RO)	20	**3824.00**	2450.00
B2B06260	Choice 20 type 3 (RO) UV	20	**4126.00**	2600.00

Specifications	
Type 2 Water Quality, MΩ-cm	1 to 15
Type 3 Water Quality, µS/cm	<40
TOC (Type 2 only), ppb	≤5
Organics Rejection Rate (Type 3 only), %	<99
Feed Water Pressure, bar	0.1 to 6
Dims, w x d x h, mm	485 x 500 x 330
Weight, kg	20

Lonza DMEM with 4.5g/L Glucose

Supplied in bottles of 500mL

OVER 50% OFF



Code	Description	List Price, £	Offer Price, £
B2B7028	With l-glutamine, sodium pyruvate and phenol red	**7.00**	3.29
B2B7030	Without l-glutamine, with sodium pyruvate and phenol red	**7.10**	3.29

Buchi R-100 Rotavapors®

1 YEAR

The Rotavapor® R-100 is a high-quality rotary evaporator to meet the essential needs in classical laboratory applications. It is capable of a manually adjustable rotation speed of 20 to 280RPM and equipped with an action jack lift for manual lifting of the evaporating flask. The optional I-100 interface is an easy to use interface that controls the vacuum digitally. It is optimally suited to on/off-regulate the vacuum pump V-100.

- Temperature range: 20 to 95°C (with heating bath B-100)
- Rotation speed: 20 to 280rpm
- Flask size range: 50 to 400mL
- Condenser types with plastic safety coating: vertical or cold trap

12% OFF



Code	Glass Assembly	I-100 Interface	B-100 Heating Bath	V-100 Pump	Recirculating Chiller	List Price, £	Offer Price, £
B2B06804	Vertical	—	—	—	—	**2448.00**	2154.00
B2B06806	Vertical	Yes	Yes	Yes	—	**4582.00**	4032.00
B2B06808	Vertical	Yes	Yes	Yes	F-100 (fixed 10°C)	**6251.00**	5501.00
B2B06810	Vertical	Yes	Yes	Yes	F-105 (-10 to -25°C)	**6778.00**	5965.00
B2B06812	Cold trap	—	—	—	—	**2589.00**	2278.00
B2B06814	Cold trap	Yes	Yes	Yes	—	**4714.00**	4148.00

Buchi V-100 Vacuum Pumps

1 YEAR

An economical and chemical-resistant PTFE diaphragm vacuum pump with a space saving design. It covers the essential needs in vacuum generation. Optimally suited to work with the Rotavapor® R-100.

- Small footprint saves valuable laboratory space
- Useable for multiple applications
- Lightweight and compact design with integrated carrying handle
- Low maintenance
- Highly chemical resistant thanks to use of quality materials
- Integrated ECO^2 mode, active after 1h with suction capacity of 1m^3/h

UP TO 12% OFF



Specifications	
Suction Capacity, m^3/h	1.5
Final Vacuum (absolute), mbar	10 (+/- 2)
Max Nominal Speed, RPM	1280
Nominal Speed in ECO^2 Mode	70% of nominal speed

Code	Description	List Price, £	Offer Price, £
B2B06816	V-100 with manual control	**1452.00**	1278.00
B2B06818	V-100 with I-100 interface	**2376.00**	2091.00
B2B7120	I-100 interface	**925.00**	833.00

Shield Scientific SMARTLine™ Nitrile Gloves

- Blue, ambidextrous, beaded cuff, finger textured
- Nitrile synthetic rubber (acrylonitrile butadiene)
- Powder-free
- Short length (240mm/9.4")
- Non-sterile
- Medical device class 1 (MDR) according to the Regulation (EU) 2017/745
- Personal Protective Equipment Category III (PPE - Complex Design) according to the Regulation (EU) 2016/425
- AQL <1.5

In Stock Now!



Supplied in cases of 1000 (10 packs of 100 gloves)

Code	Size	List Price, £
SAF12440	X small	**162.50**
SAF12460	Small	**162.50**
SAF12480	Medium	**162.50**
SAF12500	Large	**162.50**
SAF12520	X large	**162.50**



Reusable Face Masks

Premium and sustainable. Nanotech coated 3-layered 100% cotton. Washable up to 100 times.

Code	Size	List Price, £
COV1016	Large	**0.99**
COV1018	Medium	**0.99**

SLS Lab Pro Insulated Eco Drying Cabinets

1 YEAR

SLS Lab Pro eco drying cabinets are designed with energy efficiency in mind, utilising thermal insulation and a user programmable digital control, for drying laboratory glassware, surgical instruments or media.

- Energy saving thermal insulation to 5 sides
- Low power consumption
- Easy accessible control system
- Digital temperature controller
- Digital 7 day 24hr timer
- Economical to run / lower running costs
- Dual circulating fans and easy roll mounting wheels on floor standing units.
- Corrosion free stainless steel internal chamber
- Anti-microbial powder coat paint to external surfaces
- Temperature range of 30 to 80°C



20% OFF

Code	Type	Capacity, L	Airflow	Door Style	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06326	Bench	113	Static	Sliding	765 x 450 x 732	**1430.00**	1144.00
B2B06324	Bench	227	Static	Sliding	1000 x 550 x 807	**1690.00**	1352.00
B2B06328	Floor standing	426	Fan-assisted	Hinged	635 x 650 x 1870	**3348.00**	2678.00
B2B06330	Floor Standing	885	Fan-assisted	Hinged	1168 x 650 x 1870	**4445.00**	3556.00

SLS Lab Pro Water Baths

Digital water baths providing a stable temperature environment with digital PID temperature control for precision with an LED display. Controls feature auto alarm settings, illuminated on/off switch, heater and over temperature indications.

- Temperature range: ambient +5 to 99°C
- Over temperature alarm with heater cut off
- Touch pad controls with easy wipe surface
- Painted surfaces feature antibacterial protection, immersed components are corrosion resistant
- Free additional year warranty (4 years total)

Unstirred

AND 1 year warranty extension 25% OFF

- Sensitivity: ±0.2°C, uniformity: ±0.1°C

Supplied with clear, polycarbonate lid



Code	Capacity, L	Ext Dims, w x d x h, mm	Int Dims, w x d x h, mm	Drain Outlet	List Price, £	Offer Price, £
B2B7076	2	332 x 185 x 135	300 x 150 x 65	No	**436.00**	327.00
B2B06266	4	332 x 185 x 290	300 x 150 x 150	No	**492.00**	369.00
B2B06268	14	361 x 332 x 290	325 x 300 x 150	No	**578.00**	434.00
B2B06270	22	538 x 322 x 290	500 x 300 x 150	Yes	**645.00**	484.00
B2B7078	28	538 x 332 x 290	500 x 300 x 200	Yes	**720.00**	540.00

Stirred

AND 1 year warranty extension 20% OFF

- Sensitivity: ±0.05°C, uniformity: ±0.01°C
- Robust thermostirrer constructed from stainless steel for durability
- Low water level is indicated and heating is automatically suspended with an automatic restart when the bath is filled
- Can be set for water temperature or a combination of temperature and time
- Timer programmable to commence once a preset temperature is reached and setting retained once unit is turned off



Code	Capacity, L	Ext Dims, w x d x h, mm	Int Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B06272	8	271 x 332 x 170	129 x 300 x 150	**848.00**	678.00
B2B06274	14	361 x 332 x 170	219 x 298 x 150	**854.00**	683.00
B2B06276	22	537 x 332 x 170	395 x 298 x 150	**900.00**	720.00

Forehead Strip Thermometer



Forehead Strip Thermometer

Clear case. Range: 35 to 40°C, divisions: 1.0°C, accuracy: ±1.0°C.

Code	List Price, £
THE5204	**0.99**

SLS Lab Pro Analogue Ultrasonic Baths

NEW 3 YEARS

With capacities from 1.5L to 25L, the SLS Lab Pro Analogue baths offer simple analogue timer and temperature controls, providing entry level ultrasonic baths ideal for cleaning small items for use in a wide range of applications. Supplied with a stainless steel basket and plastic lid. SLS2006 has a non-adjustable heater element.

- Ambient to 70°C temperature control on heated models
- 0 - 15 minute timer
- Compact and user-friendly

20% OFF



Code	Capacity, L	Heated	Overall Dims, w x d x h, mm	Int Dims, w x d x h, mm	List Price, £	Offer Price, £
SLS2004	1.5	No	180 x 160 x 190	150 x 140 x 100	**274.00**	219.00
SLS2006	1.5	Yes	180 x 160 x 190	150 x 140 x 100	**320.00**	256.00
SLS2016	2.5	No	270 x 170 x 210	240 x 140 x 100	**351.00**	281.00
SLS2018	2.5	Yes	270 x 170 x 210	240 x 140 x 100	**406.00**	325.00
SLS2020	4.5	Yes	330 x 180 x 275	300 x 150 x 150	**681.00**	545.00
SLS2022	13	Yes	375 x 345 x 275	330 x 300 x 150	**868.00**	694.00
SLS2026	25	Yes	550 x 345 x 365	500 x 300 x 200	**1231.00**	985.00

SLS Lab Pro Digital Ultrasonic Baths

NEW 3 YEARS

With capacities from 4.5 to 25L, the SLS Lab Pro Digital baths offer precise and accurate process control of time, temperature and ultrasonic power through the LCD control panel. Incorporating frequency LEAP technology for homogeneous, repeatable ultrasonic activity throughout the tank. The SD card port means that each cycle can be validated for full process traceability via transfer to computer and provided software. Supplied with a stainless steel basket and plastic lid.

- Ambient to 70°C temperature control
- 0 - 99 minute timer
- Degas mode
- Energy saving mode
- Consistent cleaning results every time

20% OFF



Code	Capacity, L	Overall Dims, w x d x h, mm	Int Dims, w x d x h, mm	List Price, £	Offer Price, £
SLS2030	4.5	345 x 200 x 265	300 x 150 x 150	**956.00**	765.00
SLS2038	9.5	550 x 185 x 265	500 x 140 x 150	**1187.00**	950.00
SLS2040	12.5	345 x 285 x 365	295 x 245 x 200	**1364.00**	1091.00
SLS2042	13	375 x 345 x 265	330 x 300 x 150	**1375.00**	1100.00
SLS2044	17.5	375 x 345 x 365	330 x 300 x 200	**1506.00**	1205.00
SLS2046	25	550 x 345 x 365	500 x 300 x 200	**1770.00**	1416.00

SLS Lab Pro S500 Mini Recirculating Chiller

2 YEARS

LAB PRO

With a sophisticated touchscreen controller and 500W cooling power the S500 Mini is ideal for many laboratory applications. Built to save space, the Mini is about the size of the average desktop PC.

- A touchscreen interface
- Universal 90-260 VAC input voltage and 50/60Hz input frequency suitable for use all over the world
- Variable speed compressor and fan
- Whisper quiet
- Continual adjustment of refrigerant mass flow rate to control duty
- Water system constructed from 12mm push fit fittings
- USB port for downloading system data

25% OFF



Code	Temp Range, °C	Cooling Capacity, kW	Flow Rate, L/min	List Price, £	Offer Price, £
B2B06404	–10 to +60	0.5	3.5	**3285.00**	2464.00

SLS Lab Basics Mini Vacuum Pumps

1 YEAR

LAB BASICS

Single-head, dry-running devices used in a wide range of laboratory applications. They transfer, compress and pump down without contamination.

- 100% oil-free transfer
- PTFE coated version for slightly aggressive or corrosive gases and vapours
- Maintenance-free
- High level of gas tightness
- IP20 motor protection
- Silencer fitted to outlet port
- 6mm hosetail on inlet

UP TO 40% OFF



Code	Diaphragm Material	Delivery, L/min	Ultimate Vacuum, mbar	List Price, £	Offer Price, £
B2B06244	EPOM rubber	6	100	**310.00**	205.00
B2B06246	PTFE coated	5.5	160	**365.00**	220.00

Haier HLR-310F Laboratory Refrigerator

2 YEARS

Haier Biomedical
Intelligent Protection of Life Science

Upright laboratory 310L capacity refrigerator with precise temperature control and adjustable set point from 3 to 16°C. Microprocessor controller with LED display and multiple alarms. Access port, high-strength glass shelves, lock and USB interface as standard. Environmentally-friendly hydrocarbon refrigeration technology to reduces energy consumption.

- 3 to 16°C adjustable set point with one key - flexible and adaptable to meet your needs
- Internal temperature variation is within 3°C to professionally keep temperature uniformity
- Include high and low temperature alarms, door open alarm
- Tempered glass shelves



25% OFF

Code	Temp Range, °C	Capacity, L	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7292	3 - 16	310	605 x 600 x 1870	**1298.00**	974.00

Haier HYC-118 Pharmacy Refrigerator

2 YEARS

Haier Biomedical
Intelligent Protection of Life Science

Underbench pharmacy refrigerator with solid door, with microprocessor control, digital display and temperature adjustment with an increment of 0.1°C. HC controller with LED display and multiple alarms. Access port as standard.

- Audible buzzer and visible flashing light alarms
- Three alarm functions: high/low temperature, door ajar, and sensor error
- Forced air cooling for better cabinet temperature uniformity
- Auto defrost
- Optimised refrigeration system, utilising high-efficiency HC compressor significantly reduces energy consumption, HC refrigerants are natural non-toxic and more environmentally friendly

30% OFF



Code	Temp Range, °C	Capacity, L	Dims, w x d x h, mm	List Price, £	Offer Price, £
B2B7294	2 - 8	118	597 x 635 x 810	**1012.00**	708.00

Haier Biomedical Freezers

2 YEARS

Haier Biomedical
Intelligent Protection of Life Science

-25°C biomedical freezers with manual defrost and internal drawers. Reliable, energy-efficient and environmentally friendly HC refrigeration.

Featuring microprocessor controller, LED display with battery backup, alarm functions and lock.

- Efficient hydrocarbon (HC) compressor and optimised refrigeration system, with low power consumption
- Completely green refrigeration solution
- Low noise
- Secure and safe, suitable for multiple users with mechanical lock plus lock catch
- Microprocessor electronic temperature controller
- LCD digital temperature display with display precision is 0.1°C
- Temperature range: -10 to -25°C
- Multiple alarms including high and low temperature, sensor error, power failure, door ajar, high ambient and remote alarm
- Standard access port on the left side, which is convenient for users to test independently
- High density foam insulation for rigidity and stable storage temperature
- Underbench (92L) or upright (262L) models

20% OFF



Code	Model	Capacity, L	Dims, w x d x h, mm	No. of Drawers	List Price, £	Offer Price, £
B2B7298	DW-25L92	92	640 x 610 x 810	3	**891.00**	713.00
B2B7296	DW-25L262	262	700 x 705 x 1665	7	**1575.00**	1260.00

42% OFF

TAE Buffer



National Diagnostics TAE Buffer

50x concentration solution of 2M Tris-acetate and 100mM Na EDTA in distilled/deionized water (pH 8.3 at 1x concentration). 18 MegOhm water and 0.2 Micron filtration.

Code	Pack	List Price, £	Offer Price, £
B2B7046	1L	**80.00**	46.10

BACK 2 BASICS 2021

GREAT
OFFERS
INSIDE



WORLD LAND TRUST™
www.carbonbalancedpaper.com

FSC www.fsc.org
MIX
Paper from responsible sources
FSC® C017574

slsinfo@scientific-labs.com | www.scientificlabs.co.uk

SCIENTIFIC LABORATORY SUPPLIES