## Eppendorf ThermoMixer C

## FREE SmartBlock

Eppendorf ThermoMixer<sup>®</sup> C combines unique mixing performance with excellent temperature control to guarantee complete, dependable and reproducible test results. Improves user assay results by mixing and incubating samples at the same time. With quick and easy-to-exchange SmartBlocks for all common lab vessels, new and improved program functions, and a high level of stability.

- ✓ Mixing Frequency: 300 3000 RPM
- ✓ Temperature Range: 15°C below ambient to 100°C
- ✓ Temperature Accuracy: ±0.5 °C at 20 45°C
- ✓ Dims, w x d x h, mm: 206 x 304 x 136

| Code  | Description                 | List Price, £ |
|-------|-----------------------------|---------------|
| F9390 | ThermoMixer C without Block | 2097.00       |



Select one of the following FREE SmartBlocks when you purchase the ThermoMixer C (Shipped Separately)

| Code  | For tubes            |
|-------|----------------------|
| F9392 | 8 x 5.0mL            |
| F9394 | 24 x 1.5mL           |
| F9396 | 24 x 0.5mL           |
| F9398 | 24 x 2.0mL           |
| F9400 | 4 x 50mL             |
| F9402 | 8 x 15mL             |
| F9404 | 24 Cryotubes 1.5-2mL |
|       |                      |

North £435

Free

Smart Block

1 1

(prog 1) [prog 2] [prog 3] [prog 4] [prog 5]

Mix

E

eppendorf