

ID-Nr. 30678-005 Model G90.205.060.2F



Dimensions		
Width (external)	598.00 mm	
Depth (external)	615.00 mm	
Height (external)	2050.00 mm	
Width (internal)	477.00 mm	
Depth (internal)	425.00 mm	
Height (internal)	1858.00 mm	
The available internal dimensions can vary depending on the interior equipment package.		

weight / Loud	
Weight without interior equipment	365 kg
Distributed load	999.00 kg/m²
Maximum load	600 kg
Ventilation	
Extraction air	75 DN
Minimum exhaust air quantity 10 times	4 m³/h
Minimum exhaust air quantity 120 times	45 m³/h

Weight / Load

Door opening angle Depth with open doors

x 50-litre gas cylinders

Customs tariff number

For further details of the lead-through possibilities and exh	aust air please have a closer look to EN 14470-2.		
Colouring / Surface finish			
Body colour code			
Body colour	laboratory white (sim. RAL 9016)		
Body surface finish	plain		
Door / Drawer colour code			
Door / Drawer colour	laboratory white (sim. RAL 9016)		
Door / Drawer surface finish	plain		
General Information			
Number of doors	1		

180 00°

2 piece

1135 mm

94032080

G90 EN 14470-2 EX 1-4470-2 EX 1-4470-2 EX 1-44-Prob5	E

Gas cylinder cabinet G-ULTIMATE-90 Model G90.205.060.2F, laboratory white (sim. RAL 9016)

Safe and approved storage of flammable or toxic gases in working areas – for up to 2 x 50-litre gas cylinders

Function / construction:

- Robust construction and longevity: body made of powdercoated sheet steel
- Control at a glance: optional high-quality F90 glass window allowing quick view of the level and pressure of the gas cylinders
- No unauthorised use: door lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- Easy mounting of connecting pipes and gas fittings: large interior height (1890 mm), many lead-through possibilities on the top of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust, even ventilation inside the cabinet
- Tested and certified: according to the stricter GS principles

Available equipment:

 Standard interior equipment – complete with mounting rails, rolling ramp and cylinder retainer Front view Side view





