Laboratory Plus Bluetooth Enabled Freezer

242L Laboratory Plus Upright Freezer with Solid Door

GDMA code LSFSF242BT-UK SKU code 444411362





Key features

- \checkmark Local monitoring and alarm history via Bluetooth
- ✓ Lec Medical Smartphone App compatible
- \checkmark Access Port, Factory fitted 16mm porthole
- \checkmark Spark-free interior to reduce risk of ignition





Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity.



Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Spark-free

We have removed

items such as fans

interior of the fridge

igniting flammable

and lights so the

has no chance of

liquids.

Access port

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.



Anti-Microbial Handle

Anti-microbial powder coating to help prevent cross contamination by inhibiting growth of microbes.



The Experts in Medical Refrigeration

www.lec-medical.co.uk § 0344 815 3742

1of 2

Specification: 242L Laboratory Plus Upright Freezer with Solid Door

| specification. 2422 Laboratory Plus oplight Freezer with solid D | 001 |
|--|--|
| Gross Capacity (litres) | 242L |
| Net Capacity (litres) | 229L |
| Unit External Width (mm) | 595mm |
| Unit External Depth (mm) | 660mm |
| Unit External Height (mm) | 1500mm |
| Product Weight (kg) | 58.0Kg |
| Packed Width (mm) | |
| Packed Depth (mm) | 640mm |
| | 660mm |
| Packed Height (mm) | 1560mm |
| Packed Weight (kg) | 65.0Kg |
| Country of Origin | UK |
| Internal Dimensions (mm) (WxDxH) | 420mm x 455mm x 1345mm |
| Temperature Range | -18°C to -25°C |
| Colour | White/Green |
| External Finish | Painted Steel |
| Internal Finish | HIPS |
| Type of plastic | SRL800 (HIPS/ABS mix) |
| Door Finish | Painted Steel / Solid |
| Door Type | Solid |
| Door Style | Hinged, Reversible |
| Door Liner | Flat |
| Number of Door Trays | n/a |
| Number of Door Tray Positions | n/a |
| | |
| Door Open Depth (mm) | 1150mm |
| Replacement Door Seal | Yes |
| Open Door Sensor | Yes |
| Lock | Yes, 2 Keys |
| Adjustable Feet (number & position) | 2 adjustable (front) |
| Porthole | Yes |
| Porthole Size | 16 mm |
| Porthole Location | Rear Bottom |
| Temperature Display on Panel | Yes |
| Temperature Alarm | Yes |
| Remote Alarm Contacts | Yes |
| Audible Alarms | Yes |
| Visual Alarms | Yes |
| Number of Shelves/Drawers | 6 |
| Number of Shelf Positions | 6 |
| Shelf Size (mm) (WxDxH) | 495mm x 325mm x 6mm |
| Shelf Material | Glass/HIPS |
| Drawer Size (mm) (WxDxH) | 5@ 385mm x 395mm x 195mm, 1@ 385mm x 242mm x 205mm |
| Drawer Material | HIPS* |
| Interior Light | No |
| Light Type | n/a |
| Light Activation | n/a |
| | No |
| Fan Gravit Fran | |
| Spark Free | Yes |
| Defrost setting | Auto (Off Cycle) |
| Controller Type | Digital, External |
| Battery Back Up/Hours | No |
| Bluetooth | Yes |
| Number of Probes |] |
| Probe Type | Air |
| Ambient Temperature Range | 10°C to 32°C |
| Refrigerant Type | R600a |
| Voltage Supply (v) | 220-240V |
| | 80mm |
| Insulation Inickness (mm) | == |
| Insulation Thickness (mm) Insulation Type | High Density Polyurethane Foam |
| Insulation Type | High Density Polyurethane Foam |
| Insulation Type Blowing Agent | Cyclopentane |
| Insulation Type | |

