



## S 25 EC - C - 18 G Dispersing tool

/// Data Sheet

The dispersing tool S 25 EC - C - 18 G is suitable for general applications involving high speed and high shear mixing, crushing in liquid, emulsification, particle size reduction in solution and vigorous dissolving of miscible and immiscible solids and liquids in a liquid medium.

As the name "easy clean" implies, the dispersing tools are particularly easy to clean: by simply turning and lowering the clamp, the shaft and rotor can be extended from the shaft until the whole rotor comes out of the stator. Then the shaft tube of the tool can be completely rinsed from inside.







## designed for scientists

Note: S 25 EC - C - 18 G is only compatible with the dispersers T 25 easy clean digital and control. The temperature sensing function of the T tools can only be activated when used in combination with the T 25 easy clean control.











## designed for scientists

## **Technical Data**

Volume range (H2O) [I]	0.01 - 1.5	
Stator diameter [mm]	18	
Rotor diameter [mm]	12.7	
Gap between rotor and stator [mm]	0.3	
allowable Speed max. [rpm]	25000	
Circumferential speed max. [m/s]	16.6	
Immersion depth [mm]	35 - 150	
Shaft length [mm]	191	
Material in contact with medium	AISI 316L, ceramic	
pH range	2 - 13	
Suitable for solvents	yes	
Suitable for abrasive substances	yes	
Working temperature max. [°C]	180	
Sterilization methods	all methods	
Ultimate fineness, suspensions [µm]	10 - 50	
Ultimate fineness, emulsions [µm]	1 - 10	
Weight [kg]	0.4	



