

Series 1A 80

LMS by Dulas Life Sciences

Reliable and accurate temperature control.

Our cooled incubators offer optimum temperature control from -10°C to $+50^{\circ}\text{C}$ with an average variation of 0.5°C and fluctuation of 0.1°C , or 0°C to $+60^{\circ}\text{C}$ upon request.

LMS has been producing scientific incubation products since 1979.



Key Features



Door lock

Preventing unauthorised access



Defrost

Automatic, with a manual override option built in



Fruit fly modification

Prevents corrosion caused by fruit flies



Self-evaporating drip tray

For additional temperature probes



Fan assisted air circulation

Keeping temperatures consistent



Heating / Cooling control

Optimising power usage when needed

Cooled Incubator - White Interior And Exterior

Series 1A

Standard	Model	80
	RJ45 interface for remote access (wired)	Yes
	Capacity (L)	76
	Material	Powder coated mild steel
	Chamber material	Pre-coated aluminium
	Temperature range	-10°C to +50°C
	Accuracy	+0.5°C
	Height exterior (mm)	780
	Width exterior (mm)	520
	Depth exterior (mm)	680
	Shelf size (mm)	420 x 386
	Weight (kg)	40
	Number of shelves	2
Fruit fly modification	Yes	
Access porthole	Yes	
Optional extras	Programmable controller	Yes
	Dual temperature control	Yes
	Double glazed door*	No
	Inner perspex door	Yes
	Extra shelves	Yes
	Fully programmable interior illumination	Yes
	Independent 24 hour / 7 day timer	Yes
	High / low AV alarm	Yes
	Integral chart recorder	Yes
	Internal 13A socket (EU/UK)	Yes
	Drying mode	Yes
	Corrosive conditions evaporator	Yes
	Pre-programming service	Yes