Laboratory Plus Bluetooth Enabled Refrigerator

400L Laboratory Plus Upright Fridge with Solid Door

GDMA code LSFSR400BT-UK

SKU code 444411364







Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Lec Medical Smartphone App compatible
- ✓ Access Port Factory fitted 16mm porthole
- ✓ Spark-free interior to reduce risk of ignition











Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Spark-free

We have removed items such as fans and lights so the interior of the fridge has no chance of igniting flammable liquids.

Access port

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



Specification: 400L Laboratory Plus Upright Fridge with Solid Door

Gross Capacity (litres)	394L
Net Capacity (litres)	394L
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Jnit External Height (mm)	1935mm
Product Weight (kg)	61.8Kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	1995mm
Packed Weight (kg)	70.8Kg
nternal Dimensions (mm) (WxDxH)	515mm x 480mm x 1783mm
emperature Range	+2°C to +10°C
Colour	White/green
External Finish	Painted Steel
nternal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Style	Balcony
Number of Door Trays	7
Number of Door Tray Positions	13
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable (front)
Porthole	Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
/isual Alarms	Yes
Number of Shelves/Drawers	7
Number of Shelf Positions	12
Shelf Size (mm) (WxDxH)	495mm x 325mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	·
Number of Baskets	n/a 1
Basket Material	Polythene Coated Wire
Basket Naterial Basket Size (mm) (WxDxH)	·
nterior Light	485mm x 180mm x 171mm
Fan	no no
Spark Free	
•	Yes A.A. (Officerals)
Defrost setting	Auto (Off Cycle)
Controller Type Bluetooth	Digital, External
	Yes
Number of Probes	1
Probe Type	Air
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a
JK3 Pin Plug	no
Other Plug Types Available	Yes
/oltage Supply (v)	220-240V
nsulation Thickness (mm)	45mm
nsulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes

