



LABCOLD™

medical & scientific refrigeration



RLCG01503

Glass Door

Refrigerated Cooled Incubator

This 150 litre cooled incubator is ideal for microbiology or any application where precise and consistent temperatures at or below room temperature are required.

With a robust painted steel exterior and powder coated steel interior and fully adjustable shelves, this incubator is versatile and built to last with a temperature uniformity of better than $\pm 0.5^{\circ}\text{C}$ at 4°C and $\pm 1^{\circ}\text{C}$ at 20°C

This model is also available with a solid door, please see [Labcold](#) model RLSD01503.



Fully Adjustable shelves



Access Port



Door Lock



Digital Microprocessor Controller

| Part Number | RLCG01503 |
|--|------------------------------------|
| Capacity (Litres) | 150 |
| Style | Underbench |
| Exterior Dimensions (HxWxD) | 835 x 600 x 600mm |
| Interior Dimensions (HxWxD) | 690 x 480 x 410mm |
| Weight | 54kg |
| Energy Consumption | TBC kWh/24hr |
| Operating Temperature | +5°C to +40°C |
| Interior Construction | Powder Coated Steel |
| Exterior Construction | Enamelled Steel |
| Door Style | Glass |
| Door Hinging | Right |
| Lock | Manual Key |
| Shelves | 3 |
| Shelf dimension (WxD) | 2 x 475 x 385mm 1 x 475 x 245mm |
| Spare shelves available | ✓ |
| Internal Light | ✓ |
| Temperature display | ✓ |
| Microprocessor controlled temperature regulation | ✓ |
| Fan assisted temperature control | ✓ |
| Access Port | ✓ |
| Auto Defrost | X |

Labcold Cooled Incubators are also available in 88 litre, 150 litre and 600 litre capacity

Most models have the choice of glass or solid door