

93-853

Durable Nitrile Exam Glove with Extended Cuff and Advanced Barrier Protection



Extended chemical splash protection, approved for handling chemotherapy drugs

- Superior strength and durability for maximum protection against rips, snags or tears
- Low, 0.65 AQL for advanced barrier protection
- Tested for use with chemotherapy/cytotoxic drugs
- Tested against both fentanyl and gastric acid (vomit) to simulate hazardous, real world overdose situations



Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Healthcare

Recommended For

- Inspection, selecting, checking parts
- Assembly and inspection of components
- Picking and fastening components
- Equipment repair and maintenance
- General Purpose Auto Aftermarket
- Tire rotation & changes
- Animal care feeding and cleanupMaintaining lab furniture and
- equipment
- Sample taking and processing
- Administering drugs
- Raw material sample collection
- Tested for use with chemotherapy drugs
- Extra protection over the wrist and arm
- Protection from Type I latex allergy in HCW's or patients







93-853 **Durable Nitrile Exam Glove with Extended Cuff and Advanced Barrier** Protection

TECHNICAL DATA SHEET

PRODUCT INFORMATION

	93-853					
Material	Nitrile					
Color	Violet Blue					
Glove Design	Chlorinated, Powder-Free, Textured Fingers					
Cuff	Beaded					
Manufacturing/QMS Audit Standards	ISO 13485:2003					
Regulatory/Standards Compliance	Category III, EAC TP TC 019:2011, EN 1149-1/2/3, EN 374:2003, EN 420:2003 + A1:2009, EN 455 1-4, EN ISO 374-1:2016, EN ISO 374-5:2016, European Directive 89/686/EEC, ISO 11193					
Packaging	50 gloves per dispenser 10 dispensers per case 500 gloves per case *40 gloves per dispenser (Size XXXL) *400 gloves per case (Size XXXL)					
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.					
Country of Origin	Malaysia					
User Needs Segment	High Risk					
Available sizes	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11), XXXL (11.5 - 12)					
Anti-static	Yes					
Vulcanization Chemical Accelerators	• Zinc Dibutyldithiocarbamate (ZDBC) Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.					

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	295 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN 420
Finger Thickness (mm/mils)	ness (mm/mils) 0.22 / 8.7		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 30	≥ 20	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 18	≥ 18	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)	XXXL (11.5 - 12)
Product Code	93853060	93853070	93853080	93853090	93853100	93853110	93853120

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133 Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Performance Standards and Regulatory Compliance



EN ISO 374-5:2016 VIRUS

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking [©] 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

