

92-600 Robust Disposable Nitril

Robust Disposable Nitrile Glove with Enhanced Chemical Splash Protection



The world's leading disposable glove for chemical splash protection*

- The world's leading disposable glove for chemical splash protection
- Proprietary Ansell material formulation offers enhanced chemical splash protection
- Soft nitrile blend provides high levels of comfort
- Robust design for superior durability
- Silicone free for product protection
- Also available in vend pack



Industries

- Life Sciences
- Food processing
- Automotive
- Machinery and Equipment
- Chemical

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory Analysis
- Chemical Handling





I U F® TouchN ADVANCED PRODUCT & WORKER PROTECTION

92-600 **Robust Disposable Nitrile Glove with Enhanced Chemical Splash Protection**

TECHNICAL DATA SHEET

PRODUCT INFORMATION

	92-600		
Material	Nitrile		
Color	Green		
Glove Design	Powder-Free, Chlorinated, Smooth		
Cuff	Beaded		
Manufacturing/QMS Audit Standards	ISO 9001:2008		
Regulatory/Standards Compliance	ASTM D6319, Category III, EN ISO 374-1 Type B, EN 420:2003 + A1:2009, EN ISO 374-5 Virus, FDA21 CFR 177-2600, Food Type: Rubber, ISO 9001		
Packaging	100 gloves per dispenser 10 dispensers per case 1000 gloves per case		
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition		
Country of Origin	Sri Lanka		
User Needs Segment	Robust		
Available sizes	S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)		

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN420
Freedom from Holes (Inspection level I)	4.0 AQL (Americas) / 1.5 AQL (Outside of Americas)		ASTM D5151
Palm Thickness (mm/inches)	0.12 / 4.7		ASTM D3767,EN420
Finger Thickness (mm/inches)	0.08 / 3.1		ASTM D3767,EN420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 18	≥ 18	ASTM D412
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6	≥ 6	EN 455-2

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Asia Pacific Region Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 63000 Cyberjaya Selangor, Malaysia T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445 Latin America & Carbbean Region

Ansell Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C, Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia Australia T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ahcenn PYC 123610 Poccnr, Mockba Kpachonpechehckar Ha6. 12, n.3, op. 1304A Ten. +7 495 258 13 16

Technology



Performance Standards and Regulatory Compliance



Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2019 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

