Technical Specification



Product: Code: PRODUCT	SureGuard Disposable Coat DNWH10	Image: state of the state of	2	
		closure. CE marked to type PB[6], PPE Category III.		
Intended Use		Single use cleanroom coat		
Pack Format		Individually bagged 25 coats per carton		
Carton Label Information and Traceability		 Product description Product code Size Pack quantity MEAS GW NW Batch number Barcode 		
Carton Specification		Dimensions (mm) = 320 x 280 x 300 Weight(kg) = 3.5 - 5.0		
Issue: 3 Date: 03/08/2017 Page: 1 of 2		www.micronclean.com		



TECHNICAL INFORMATION

PPE category III, Type PB[6] limited splash protective coat
White microporous polypropylene with polyethylene laminate fabric
Basic weight : 60g/m² typical
Seam Strength: >50<75N
Abrasion Resistance: >100<500 cycles
Trapezoidal Tear Resistance: >20<40N
Tensile Strength: >30<60N
Puncture Resistance: >10<50N
Surface Resistance: ≤2.5 x 109
Resistance to Penetration to Liquid: <1%
Repellency to Liquid: 90%-95%/>95%
Primary packaged in polythene bags
Non-sterile
Product supplied under BS EN ISO 9001:2008 registered systems
Store in a dry, well-ventilated area in ambient conditions
Non-hazardous

Contact Details

Micronclean

Roman Bank Skegness Lincolnshire PE25 1SQ UK

Tel: +44 (0) 1754 767377 orders@micronclean.co.uk