

Product data sheet

✉ sales@brannan.co.uk

☎ +44 (0)1946 816600

🌐 brannan.co.uk

BATCH SAMPLING THERMOMETERS

These precision test thermometers are sealed into a 30ml polypropylene bottle and are ideally suited to monitor the temperature of samples in controlled storage. The 'bottle' base of the assembly maintains a core temperature similar to that of the samples being monitored and is unaffected by short term fluctuations caused by thermostatic variations or through the opening of cabinet doors. Brannan's unique **LO-tox™** blue filling eliminates the risk of mercury contamination. A variety of ranges are available covering critical temperature spans for specific applications.

Supplied with Batch Sampling Thermometer Statement of Accuracy. Bottle should be filled with monopropylene glycol or other heat transfer medium before use.

Product features:

- Non hazardous **LO-tox™** filling
- Temperature measurement unaffected by short term fluctuations
- Supplied with statement of accuracy
- Made in England

Product specifications:

Range:	See table
Accuracy:	See table
CE/ROHS/WEEE:	N/A
Hazard information (SDS):	See brannan.co.uk for information
Product material:	Bottle: Polypropylene Glass tube filling: LO-tox™ filling
Product weight:	Net: 55.5g Gross: 68.5g
Product dimensions :	Net: 145mm x 35mm diameter Gross: 153mm x 37mm x 37mm
Display box weight:	13g



Description	Range	Accuracy	Divisions	Barcode	Product no
Blood bank thermometer	-5 to +20°C	+/- 0.7°C	0.5°C	5 011405 221001	22/100/2
Freezer thermometer	-30 to 0°C	+/- 0.7°C	0.5°C	5 011405 221018	22/101/2
Refrigerator thermometer	-5 to +20°C	+/- .0.7°C	0.5°C	5 011405 221032	22/103/2
Incubator thermometer	+18 to +50°C	+/- 0.5°C	1.0°C	5 011405 221056	22/105/2

Product data sheet

✉ sales@brannan.co.uk

☎ +44 (0)1946 816600

🌐 brannan.co.uk

MAX MIN DIGITAL READING SAMPLING THERMOMETERS

All the above batch sampling thermometers are available with the maximum/minimum reading digital thermometer.

The twin reading electronic thermometer has max/min feature and high/low temperature alarm setting. Ideally suited to read temperature in a fridge or freezer or outdoor temperature and room temperature simultaneously.

Magnet attachment and 2m probe cable.
Please contact our sales team for further details.

Meter Range: -50 to +70°C&F (switchable).
Dimensions: 63mm x 63mm x 15mm
LCD Dimensions: 21 x 47mm
Product Number: 22/106/3



See data sheet for product 22/420/3 for detailed information on the digital thermometer.

Description	Barcode	Product No
Max min digital reading sampling thermometer	5 011405 221063	22/106/3

View me on
the website

