

# SLS Lab Pro Type 3 (PurA-Q Primo)

## Type 3 RO Water System

- Up to 50% water recovery rate
- Low running costs
- One easy-change pre-filter
- Mount on bench, wall or on top of a reservoir
- Intuitive, icon-based, interactive user interface with touchscreen
- Integrated leak detector and boost pump
- Choice of storage reservoir size



Code	Description
WAT2008	Primo - Type III Water System - 20L/hr

## Accessories

Code	Description
WAT2444	30 Litre Tank
WAT2446	60 Litre Tank
WAT2168	100 Litre Tank
WAT2170	100 Litre Tank with Pump - 230V
WAT2172	Valve Kit for Washing Machine Feed (Single POU)
WAT2452	Wall Mounting Kit
WAT2453	External Pre-filter Housing Kit (Excludes Filter)
WAT2173	Valve Kit for Washing Machine Feed (Double POU)



## Consumables

Code	Description
WAT2423	Pre-treatment Module - *annual change
WAT2430	Tank Vent Filter - *annual change

## Model Specifications

Model	RO Make-up Rate (@15°C)	Inorganics Rejection Rate	RO Quality (@25°C)	Dispense Rate (@15°C from tank)
Primo - Type III Water System	20L/hr	98%**	<40µS/cm	3 - 7L/min*

\* Depending on tank and pump setup \*\* Depending on feedwater impurities

## Applications

Type 3 Water Applications
Autoclave feed Glasswasher feed Feed to Ultrapure Water Systems Hydroponics Steam Generators

Dimensions			Feed Water Requirements		Services Required
Width	Height	Depth	Pressure	0.1 – 6 Bar	
490mm	500mm	290mm	Resistivity	<1400 µS-cm	
Weight (Empty)			Colloid Index	<3 SDI	
23kg			Free-chlorine & Iron	0.1 Mg/L	